

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

|                 |                                       |
|-----------------|---------------------------------------|
| Product form    | : Mixture                             |
| Product name    | : FRAG0018 Black Cherry Fragrance Oil |
| UFI             | : FRAG0018 Black Cherry Fragrance Oil |
| Product code    | : EU33753F                            |
| Type of product | : Perfumes, Fragrances                |
| Product group   | : Finished Good                       |

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

|                                  |                                           |
|----------------------------------|-------------------------------------------|
| Main use category                | : Industrial use, Professional use        |
| Industrial/Professional use spec | : For professional use only<br>Industrial |
| Use of the substance/mixture     | : Perfumes, Fragrances                    |
| Function or use category         | : Odour agents                            |

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Supplies for Candles Ltd, Unit E Swinton Bridge Industrial Estate, Whitelee, Road, Swinton,  
South Yorkshire, S64 8BH, UK

#### 1.4. Emergency telephone number

01709 257151

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

|                                                                  |      |
|------------------------------------------------------------------|------|
| Skin sensitization, Category 1                                   | H317 |
| Hazardous to the aquatic environment - Chronic Hazard Category 3 | H412 |
| Full text of H statements : see section 16                       |      |

##### Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects. May cause an allergic skin reaction.

#### 2.2. Label elements

##### Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP)

: Warning

Contains

: Citronellol Pure; Damascenone Total; Geranyl acetate; Hexyl salicylate; Iso E Super; L-Carvone; Nerol; Orange oil ; Trimofix O

### Hazard statements (CLP)

: H317 - May cause an allergic skin reaction.  
H412 - Harmful to aquatic life with long lasting effects.

### Precautionary statements (CLP)

: P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                                                                  | Product identifier                                                                                     | %            | Classification according to Regulation (EC) No. 1272/2008 [CLP]                                                                          |
|-----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|--------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Benzene carboxaldehyde                                                | (CAS-No.) 100-52-7<br>(EC-No.) 202-860-4<br>(EC Index-No.) 605-012-00-5<br>(REACH-no) 01-2119455540-44 | 14.25 – 28.5 | Acute Tox. 4 (Oral), H302                                                                                                                |
| methyl anthranilate                                                   | (CAS-No.) 134-20-3<br>(EC-No.) 205-132-4                                                               | 1.675 – 3.35 | Eye Irrit. 2, H319                                                                                                                       |
| Phenylmethanol                                                        | (CAS-No.) 100-51-6<br>(EC-No.) 202-859-9<br>(EC Index-No.) 603-057-00-5<br>(REACH-no) 01-2119492630-38 | 1.625 – 3.25 | Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Inhalation), H332                                                                             |
| Veltol plus crystals                                                  | (CAS-No.) 4940-11-8<br>(EC-No.) 225-582-5                                                              | 1 – 2        | Acute Tox. 4 (Oral), H302                                                                                                                |
| Iso E Super                                                           | (CAS-No.) 54464-57-2<br>(EC-No.) 259-174-3<br>(REACH-no) 01-2119489989-04                              | 0.925 – 1.85 | Skin Sens. 1, H317<br>Aquatic Chronic 2, H411                                                                                            |
| Leaf alcohol                                                          | (CAS-No.) 928-96-1<br>(EC-No.) 213-192-8                                                               | 0.75 – 1.5   | Flam. Liq. 3, H226<br>Eye Irrit. 2, H319                                                                                                 |
| Orange oil                                                            | (CAS-No.) 8008-57-9<br>(EC-No.) 232-433-8<br>(REACH-no) 01-2119493353-35                               | 0.75 – 1.5   | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>Asp. Tox. 1, H304<br>Aquatic Acute 1, H400<br>Aquatic Chronic 2, H411 |
| Hexyl salicylate                                                      | (CAS-No.) 6259-76-3<br>(EC-No.) 228-408-6                                                              | 0.325 – 0.65 | Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>Aquatic Chronic 1, H410                                                                     |
| Diphenyl oxide<br>substance with a Community workplace exposure limit | (CAS-No.) 101-84-8<br>(EC-No.) 202-981-2<br>(REACH-no) 01-2119472545-33                                | 0.2 – 0.4    | Eye Irrit. 2, H319<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                   |
| Cedarwood oil, Texas                                                  | (CAS-No.) 68990-83-0<br>(EC-No.) 294-461-7;614-888-8                                                   | 0.175 – 0.35 | Asp. Tox. 1, H304<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                    |

|                   |                                                                          |              |                                                                         |
|-------------------|--------------------------------------------------------------------------|--------------|-------------------------------------------------------------------------|
| Amyl salicylate   | (CAS-No.) 2050-08-0<br>(EC-No.) 218-080-2<br>(REACH-no) 01-2119969444-27 | 0.15 – 0.3   | Acute Tox. 4 (Oral), H302<br>Aquatic Chronic 1, H410                    |
| Trimofix O        | (CAS-No.) 144020-22-4<br>(EC-No.) 482-330-9                              | 0.15 – 0.3   | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410<br>Skin Sens. 1B, H317 |
| Citronellol Pure  | (CAS-No.) 106-22-9<br>(EC-No.) 203-375-0<br>(REACH-no) 01-2119453995-23  | 0.075 – 0.15 | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1B, H317        |
| Damascenone Total | (CAS-No.) 23696-85-7<br>(EC-No.) 245-833-2                               | 0.075 – 0.15 | Skin Sens. 1, H317<br>Aquatic Chronic 2, H411                           |
| L-Carvone         | (CAS-No.) 6485-40-1<br>(EC-No.) 229-352-5<br>(EC Index-No.) 606-148-00-8 | 0.075 – 0.15 | Skin Sens. 1B, H317                                                     |
| Nerol             | (CAS-No.) 106-25-2<br>(EC-No.) 203-378-7                                 | 0.075 – 0.15 | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317         |
| Geranyl acetate   | (CAS-No.) 105-87-3<br>(EC-No.) 203-341-5<br>(REACH-no) 01-2119973480-35  | 0.05 – 0.1   | Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>Aquatic Chronic 3, H412    |

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures general            | : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).                                                                                                                                                                                                                                                                                                                  |
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.                                                                                                                                                                                                                                                                                                             |
| First-aid measures after skin contact | : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact  | : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.                                                                                                                                                                                                                                                                                                   |
| First-aid measures after ingestion    | : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center/doctor/physician if you feel unwell.                                                                                                                                                                                                                                                                                                               |

### 4.2. Most important symptoms and effects, both acute and delayed

|                                     |                                                                                            |
|-------------------------------------|--------------------------------------------------------------------------------------------|
| Symptoms/effects                    | : Not expected to present a significant hazard under anticipated conditions of normal use. |
| Symptoms/effects after skin contact | : May cause an allergic skin reaction.                                                     |

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

|                                |                                                        |
|--------------------------------|--------------------------------------------------------|
| Suitable extinguishing media   | : Water spray. Dry powder. Foam. Carbon dioxide. Sand. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.                     |

### 5.2. Special hazards arising from the substance or mixture

|             |                       |
|-------------|-----------------------|
| Fire hazard | : Combustible liquid. |
|-------------|-----------------------|

- |                                                  |                                                   |
|--------------------------------------------------|---------------------------------------------------|
| Explosion hazard                                 | : May form flammable/explosive vapor-air mixture. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released.                    |

### 5.3. Advice for firefighters

- |                                |                                                                                                                                                                                                                                        |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Firefighting instructions      | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.                                                                      |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- |                  |                                                                                                           |
|------------------|-----------------------------------------------------------------------------------------------------------|
| General measures | : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. |
|------------------|-----------------------------------------------------------------------------------------------------------|

#### 6.1.1. For non-emergency personnel

- |                      |                                                                                                                                               |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Emergency procedures | : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|

#### 6.1.2. For emergency responders

- |                      |                                                                                                                                                                                                        |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Ventilate area.                                                                                                                                                                                      |

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- |                         |                                                                                                                                                                                              |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Methods for cleaning up | : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. |
| Other information       | : Dispose of materials or solid residues at an authorized site.                                                                                                                              |

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- |                                   |                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional hazards when processed | : Handle empty containers with care because residual vapors are flammable. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.                                                                                                                                                                                                                                                   |
| Precautions for safe handling     | : Ensure good ventilation of the work station. Wear personal protective equipment. No open flames. No smoking. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. |
| Hygiene measures                  | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.                                                                                                                                                                             |

### 7.2. Conditions for safe storage, including any incompatibilities

- |                    |                                                                                                                                                                                                                                                                                                |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Technical measures | : Proper grounding procedures to avoid static electricity should be followed.                                                                                                                                                                                                                  |
| Storage conditions | : Keep in fireproof place. Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool. |

|                            |                                                           |
|----------------------------|-----------------------------------------------------------|
| Incompatible products      | : Strong bases. Strong acids.                             |
| Incompatible materials     | : Heat sources. Sources of ignition. Direct sunlight.     |
| Storage temperature        | : 25 °C                                                   |
| Storage area               | : Store in a well-ventilated place. Store away from heat. |
| Special rules on packaging | : Store in a closed container.                            |
| Packaging materials        | : Do not store in corrodable metal.                       |

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

| Benzene carboxaldehyde (100-52-7)        |            |
|------------------------------------------|------------|
| Bulgaria - Occupational Exposure Limits  |            |
| OEL TWA                                  | 5 mg/m³    |
| Finland - Occupational Exposure Limits   |            |
| HTP (OEL TWA) [1]                        | 4.4 mg/m³  |
| HTP (OEL TWA) [2]                        | 1 ppm      |
| OEL Ceiling                              | 17.4 mg/m³ |
| OEL Ceiling [ppm]                        | 4 ppm      |
| Hungary - Occupational Exposure Limits   |            |
| AK (OEL TWA)                             | 5 mg/m³    |
| CK (OEL STEL)                            | 10 mg/m³   |
| Latvia - Occupational Exposure Limits    |            |
| OEL TWA                                  | 5 mg/m³    |
| Lithuania - Occupational Exposure Limits |            |
| IPRV (OEL TWA)                           | 5 mg/m³    |
| Poland - Occupational Exposure Limits    |            |
| NDS (OEL TWA)                            | 10 mg/m³   |
| NDSch (OEL STEL)                         | 40 mg/m³   |

| Phenylmethanol (100-51-6)                         |                                                                                                           |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Bulgaria - Occupational Exposure Limits           |                                                                                                           |
| OEL TWA                                           | 5 mg/m³                                                                                                   |
| Czech Republic - Occupational Exposure Limits     |                                                                                                           |
| PEL (OEL TWA)                                     | 40 mg/m³                                                                                                  |
| Finland - Occupational Exposure Limits            |                                                                                                           |
| HTP (OEL TWA) [1]                                 | 45 mg/m³                                                                                                  |
| HTP (OEL TWA) [2]                                 | 10 ppm                                                                                                    |
| Germany - Occupational Exposure Limits (TRGS 900) |                                                                                                           |
| AGW (OEL TWA) [1]                                 | 22 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) |
| AGW (OEL TWA) [2]                                 | 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)    |

| Phenylmethanol (100-51-6)                          |                                        |
|----------------------------------------------------|----------------------------------------|
| Chemical category                                  | skin notation                          |
| Latvia - Occupational Exposure Limits              |                                        |
| OEL TWA                                            | 5 mg/m <sup>3</sup>                    |
| Lithuania - Occupational Exposure Limits           |                                        |
| IPRV (OEL TWA)                                     | 5 mg/m <sup>3</sup>                    |
| Chemical category                                  | skin notation                          |
| Poland - Occupational Exposure Limits              |                                        |
| NDS (OEL TWA)                                      | 240 mg/m <sup>3</sup>                  |
| Slovenia - Occupational Exposure Limits            |                                        |
| OEL TWA                                            | 22 mg/m <sup>3</sup>                   |
| OEL TWA [ppm]                                      | 5 ppm                                  |
| OEL STEL                                           | 44 mg/m <sup>3</sup>                   |
| OEL STEL [ppm]                                     | 10 ppm                                 |
| Chemical category                                  | Potential for cutaneous absorption     |
| Switzerland - Occupational Exposure Limits         |                                        |
| MAK (OEL TWA) [1]                                  | 22 mg/m <sup>3</sup> (aerosol, vapour) |
| MAK (OEL TWA) [2]                                  | 5 ppm (aerosol, vapour)                |
| Chemical category                                  | skin notation                          |
| Diphenyl oxide (101-84-8)                          |                                        |
| EU - Indicative Occupational Exposure Limit (IOEL) |                                        |
| IOEL TWA                                           | 7 mg/m <sup>3</sup>                    |
| IOEL TWA [ppm]                                     | 1 ppm                                  |
| IOEL STEL                                          | 14 mg/m <sup>3</sup>                   |
| IOEL STEL [ppm]                                    | 2 ppm                                  |
| Austria - Occupational Exposure Limits             |                                        |
| MAK (OEL TWA)                                      | 7 mg/m <sup>3</sup>                    |
| MAK (OEL TWA) [ppm]                                | 1 ppm                                  |
| MAK (OEL STEL)                                     | 14 mg/m <sup>3</sup>                   |
| MAK (OEL STEL) [ppm]                               | 2 ppm                                  |
| Belgium - Occupational Exposure Limits             |                                        |
| OEL TWA                                            | 7 mg/m <sup>3</sup> (vapor)            |
| OEL TWA [ppm]                                      | 1 ppm (vapor)                          |
| OEL STEL                                           | 14 mg/m <sup>3</sup> (vapor)           |
| OEL STEL [ppm]                                     | 2 ppm (vapor)                          |
| Bulgaria - Occupational Exposure Limits            |                                        |
| OEL TWA                                            | 7 mg/m <sup>3</sup>                    |
| OEL TWA [ppm]                                      | 1 ppm                                  |
| OEL STEL                                           | 14 mg/m <sup>3</sup>                   |
| OEL STEL [ppm]                                     | 2 ppm                                  |

| Diphenyl oxide (101-84-8)                         |                                                                                                                              |
|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Croatia - Occupational Exposure Limits            |                                                                                                                              |
| GVI (OEL TWA) [1]                                 | 7 mg/m <sup>3</sup>                                                                                                          |
| GVI (OEL TWA) [2]                                 | 1 ppm                                                                                                                        |
| KGVI (OEL STEL)                                   | 14 mg/m <sup>3</sup>                                                                                                         |
| KGVI (OEL STEL) [ppm]                             | 2 ppm                                                                                                                        |
| Cyprus - Occupational Exposure Limits             |                                                                                                                              |
| OEL TWA                                           | 7 mg/m <sup>3</sup>                                                                                                          |
| OEL TWA [ppm]                                     | 1 ppm                                                                                                                        |
| OEL STEL                                          | 14 mg/m <sup>3</sup>                                                                                                         |
| OEL STEL [ppm]                                    | 2 ppm                                                                                                                        |
| Czech Republic - Occupational Exposure Limits     |                                                                                                                              |
| PEL (OEL TWA)                                     | 5 mg/m <sup>3</sup>                                                                                                          |
| Denmark - Occupational Exposure Limits            |                                                                                                                              |
| OEL TWA [1]                                       | 7 mg/m <sup>3</sup>                                                                                                          |
| OEL TWA [2]                                       | 1 ppm                                                                                                                        |
| Estonia - Occupational Exposure Limits            |                                                                                                                              |
| OEL TWA                                           | 7 mg/m <sup>3</sup>                                                                                                          |
| OEL TWA [ppm]                                     | 1 ppm                                                                                                                        |
| OEL STEL                                          | 14 mg/m <sup>3</sup>                                                                                                         |
| OEL STEL [ppm]                                    | 2 ppm                                                                                                                        |
| Finland - Occupational Exposure Limits            |                                                                                                                              |
| HTP (OEL TWA) [1]                                 | 7 mg/m <sup>3</sup>                                                                                                          |
| HTP (OEL TWA) [2]                                 | 1 ppm                                                                                                                        |
| HTP (OEL STEL)                                    | 14 mg/m <sup>3</sup>                                                                                                         |
| HTP (OEL STEL) [ppm]                              | 2 ppm                                                                                                                        |
| France - Occupational Exposure Limits             |                                                                                                                              |
| VME (OEL TWA)                                     | 7 mg/m <sup>3</sup>                                                                                                          |
| VME (OEL TWA) [ppm]                               | 1 ppm                                                                                                                        |
| Germany - Occupational Exposure Limits (TRGS 900) |                                                                                                                              |
| AGW (OEL TWA) [1]                                 | 7.1 mg/m <sup>3</sup> (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-vapor) |
| AGW (OEL TWA) [2]                                 | 1 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-vapor)                 |
| Gibraltar - Occupational Exposure Limits          |                                                                                                                              |
| OEL TWA                                           | 7 mg/m <sup>3</sup>                                                                                                          |
| OEL TWA [ppm]                                     | 1 ppm                                                                                                                        |
| OEL STEL                                          | 14 mg/m <sup>3</sup>                                                                                                         |
| OEL STEL [ppm]                                    | 200 ppm                                                                                                                      |
| Greece - Occupational Exposure Limits             |                                                                                                                              |
| OEL TWA                                           | 7 mg/m <sup>3</sup>                                                                                                          |
| OEL TWA [ppm]                                     | 1 ppm                                                                                                                        |

| Diphenyl oxide (101-84-8)                  |                                               |
|--------------------------------------------|-----------------------------------------------|
| OEL STEL                                   | 14 mg/m <sup>3</sup>                          |
| OEL STEL [ppm]                             | 2 ppm                                         |
| Hungary - Occupational Exposure Limits     |                                               |
| AK (OEL TWA)                               | 7 mg/m <sup>3</sup>                           |
| CK (OEL STEL)                              | 14 mg/m <sup>3</sup>                          |
| Ireland - Occupational Exposure Limits     |                                               |
| OEL TWA [1]                                | 7 mg/m <sup>3</sup> (vapour)                  |
| OEL TWA [2]                                | 1 ppm (vapour)                                |
| OEL STEL                                   | 14 mg/m <sup>3</sup> (vapour)                 |
| OEL STEL [ppm]                             | 2 ppm (vapour)                                |
| Latvia - Occupational Exposure Limits      |                                               |
| OEL TWA                                    | 7 mg/m <sup>3</sup>                           |
| OEL TWA [ppm]                              | 1 ppm                                         |
| Lithuania - Occupational Exposure Limits   |                                               |
| IPRV (OEL TWA)                             | 7 mg/m <sup>3</sup>                           |
| IPRV (OEL TWA) [ppm]                       | 1 ppm                                         |
| TPRV (OEL STEL)                            | 14 mg/m <sup>3</sup>                          |
| TPRV (OEL STEL) [ppm]                      | 2 ppm                                         |
| Luxembourg - Occupational Exposure Limits  |                                               |
| OEL TWA                                    | 7 mg/m <sup>3</sup>                           |
| OEL TWA [ppm]                              | 1 ppm                                         |
| OEL STEL                                   | 14 mg/m <sup>3</sup>                          |
| OEL STEL [ppm]                             | 2 ppm                                         |
| Malta - Occupational Exposure Limits       |                                               |
| OEL TWA                                    | 7 mg/m <sup>3</sup>                           |
| OEL TWA [ppm]                              | 1 ppm                                         |
| OEL STEL                                   | 14 mg/m <sup>3</sup>                          |
| OEL STEL [ppm]                             | 2 ppm                                         |
| Netherlands - Occupational Exposure Limits |                                               |
| MAC-TGG (OEL TWA)                          | 7 mg/m <sup>3</sup>                           |
| MAC-15 (OEL STEL)                          | 14 mg/m <sup>3</sup>                          |
| Poland - Occupational Exposure Limits      |                                               |
| NDS (OEL TWA)                              | 7 mg/m <sup>3</sup>                           |
| NDSch (OEL STEL)                           | 14 mg/m <sup>3</sup>                          |
| Portugal - Occupational Exposure Limits    |                                               |
| OEL TWA                                    | 7 mg/m <sup>3</sup>                           |
| OEL TWA [ppm]                              | 1 ppm (vapor)                                 |
| OEL STEL                                   | 14 mg/m <sup>3</sup> (indicative limit value) |
| OEL STEL [ppm]                             | 2 ppm (indicative limit value-vapor)          |

| Diphenyl oxide (101-84-8)                     |                                                               |
|-----------------------------------------------|---------------------------------------------------------------|
| Romania - Occupational Exposure Limits        |                                                               |
| OEL TWA                                       | 5 mg/m <sup>3</sup>                                           |
| OEL TWA [ppm]                                 | 0.7 ppm                                                       |
| OEL STEL                                      | 10 mg/m <sup>3</sup>                                          |
| OEL STEL [ppm]                                | 1.4 ppm                                                       |
| Slovakia - Occupational Exposure Limits       |                                                               |
| NPHV (OEL TWA) [1]                            | 7 mg/m <sup>3</sup>                                           |
| NPHV (OEL TWA) [2]                            | 1 ppm                                                         |
| NPHV (OEL C)                                  | 7.1 mg/m <sup>3</sup>                                         |
| Slovenia - Occupational Exposure Limits       |                                                               |
| OEL TWA                                       | 7 mg/m <sup>3</sup>                                           |
| OEL TWA [ppm]                                 | 1 ppm                                                         |
| OEL STEL                                      | 14 mg/m <sup>3</sup>                                          |
| OEL STEL [ppm]                                | 2 ppm                                                         |
| Spain - Occupational Exposure Limits          |                                                               |
| VLA-ED (OEL TWA) [1]                          | 7.1 mg/m <sup>3</sup> (vapor)                                 |
| VLA-ED (OEL TWA) [2]                          | 1 ppm (vapor)                                                 |
| VLA-EC (OEL STEL)                             | 14.2 mg/m <sup>3</sup> (vapor)                                |
| VLA-EC (OEL STEL) [ppm]                       | 2 ppm (vapor)                                                 |
| Sweden - Occupational Exposure Limits         |                                                               |
| NGV (OEL TWA)                                 | 7 mg/m <sup>3</sup>                                           |
| NGV (OEL TWA) [ppm]                           | 1 ppm                                                         |
| KTV (OEL STEL)                                | 14 mg/m <sup>3</sup>                                          |
| KTV (OEL STEL) [ppm]                          | 2 ppm                                                         |
| United Kingdom - Occupational Exposure Limits |                                                               |
| WEL TWA (OEL TWA) [1]                         | 7.1 mg/m <sup>3</sup> (vapour)                                |
| WEL TWA (OEL TWA) [2]                         | 1 ppm (vapour)                                                |
| WEL STEL (OEL STEL)                           | 21.3 mg/m <sup>3</sup> (calculated-vapour)                    |
| WEL STEL (OEL STEL) [ppm]                     | 3 ppm (calculated-vapour)                                     |
| Norway - Occupational Exposure Limits         |                                                               |
| Grenseverdi (OEL TWA) [1]                     | 7 mg/m <sup>3</sup>                                           |
| Grenseverdi (OEL TWA) [2]                     | 1 ppm                                                         |
| Korttidsverdi (OEL STEL)                      | 14 mg/m <sup>3</sup> (value calculated)                       |
| Korttidsverdi (OEL STEL) [ppm]                | 2 ppm (value calculated)                                      |
| Switzerland - Occupational Exposure Limits    |                                                               |
| MAK (OEL TWA) [1]                             | 7 mg/m <sup>3</sup> (aerosol, vapour)                         |
| MAK (OEL TWA) [2]                             | 1 ppm (aerosol, vapour)                                       |
| KZGW (OEL STEL)                               | 7 mg/m <sup>3</sup> (aerosol, vapour)                         |
| KZGW (OEL STEL) [ppm]                         | 1 ppm (aerosol, vapour)                                       |
| Chemical category                             | Category 2 developmental toxin, Category 2 reproductive toxin |

### Diphenyl oxide (101-84-8)

#### USA - ACGIH - Occupational Exposure Limits

|                      |                        |
|----------------------|------------------------|
| ACGIH OEL TWA [ppm]  | 1 ppm (vapor)          |
| ACGIH OEL STEL [ppm] | 2 ppm (vapor fraction) |

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment:

Avoid all unnecessary exposure.

##### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

##### Eye protection:

Chemical goggles or safety glasses. Safety glasses

##### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Wear protective gloves.

##### 8.2.2.3. Respiratory protection

##### Respiratory protection:

Wear appropriate mask

##### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

##### Environmental exposure controls:

Avoid release to the environment.

##### Other information:

Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|                                                 |                                   |
|-------------------------------------------------|-----------------------------------|
| Physical state                                  | : Liquid                          |
| Color                                           | : light yellow. amber.            |
| Odor                                            | : characteristic.                 |
| Odor threshold                                  | : No data available               |
| pH                                              | : No data available               |
| Relative evaporation rate (butyl acetate=1)     | : No data available               |
| Melting point                                   | : Not applicable                  |
| Freezing point                                  | : No data available               |
| Boiling point                                   | : No data available               |
| Flash point                                     | : 65.9 °C (closed cup) ASTM D7094 |
| Auto-ignition temperature                       | : No data available               |
| Decomposition temperature                       | : No data available               |
| Flammability (solid, gas)                       | : Not applicable                  |
| Vapor pressure                                  | : No data available               |
| Relative vapor density at 20 °C                 | : No data available               |
| Relative density                                | : ≈ 0.97                          |
| Solubility                                      | : No data available               |
| Partition coefficient n-octanol/water (Log Pow) | : No data available               |
| Viscosity, kinematic                            | : No data available               |
| Viscosity, dynamic                              | : No data available               |
| Explosive properties                            | : No data available               |
| Oxidizing properties                            | : No data available               |
| Explosion limits                                | : No data available               |

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture. Not established.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks. Extremely high or low temperatures.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

May release flammable gases. fume. Carbon monoxide. Carbon dioxide.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| Amyl salicylate (2050-08-0) |                        |
|-----------------------------|------------------------|
| LD50 oral rat               | 4100 mg/kg             |
| LD50 oral                   | 2000 mg/kg body weight |
| LD50 dermal rabbit          | > 5000 mg/kg           |

| Benzene carboxaldehyde (100-52-7) |              |
|-----------------------------------|--------------|
| LD50 oral rat                     | 1292 mg/kg   |
| LD50 dermal rabbit                | > 1250 mg/kg |

| Phenylmethanol (100-51-6) |                        |
|---------------------------|------------------------|
| LD50 oral rat             | 1230 mg/kg             |
| LD50 oral                 | 1620 mg/kg body weight |
| LD50 dermal               | 2500 mg/kg body weight |

| Citronellol Pure (106-22-9) |                        |
|-----------------------------|------------------------|
| LD50 oral rat               | 3450 mg/kg             |
| LD50 oral                   | 3450 mg/kg body weight |
| LD50 dermal rabbit          | 2650 mg/kg             |
| LD50 dermal                 | 2650 mg/kg body weight |

| Diphenyl oxide (101-84-8)         |                        |
|-----------------------------------|------------------------|
| LD50 oral rat                     | 2450 mg/kg             |
| LD50 oral                         | 2830 mg/kg body weight |
| LD50 dermal rabbit                | > 7940 mg/kg           |
| LC50 Inhalation - Rat (Dust/Mist) | 1.5 mg/l/4h            |

| Damascenone Total (23696-85-7) |                        |
|--------------------------------|------------------------|
| LD50 dermal                    | 2900 mg/kg body weight |

| Geranyl acetate (105-87-3) |            |
|----------------------------|------------|
| LD50 oral rat              | 6330 mg/kg |

| Nerol (106-25-2)   |                        |
|--------------------|------------------------|
| LD50 oral rat      | 4500 mg/kg             |
| LD50 oral          | 4500 mg/kg body weight |
| LD50 dermal rabbit | > 5 g/kg               |

| methyl anthranilate (134-20-3) |                        |
|--------------------------------|------------------------|
| LD50 oral rat                  | 2910 mg/kg             |
| LD50 oral                      | 2780 mg/kg body weight |
| LD50 dermal rabbit             | 5000 mg/kg             |

### Hexyl salicylate (6259-76-3)

|               |          |
|---------------|----------|
| LD50 oral rat | > 5 g/kg |
|---------------|----------|

### L-Carvone (6485-40-1)

|               |                        |
|---------------|------------------------|
| LD50 oral rat | 5400 mg/kg             |
| LD50 dermal   | 3800 mg/kg body weight |

### Leaf alcohol (928-96-1)

|                    |            |
|--------------------|------------|
| LD50 oral rat      | 4700 mg/kg |
| LD50 dermal rabbit | 5000 mg/kg |

### Trimofix O (144020-22-4)

|               |              |
|---------------|--------------|
| LD50 oral rat | > 5000 mg/kg |
|---------------|--------------|

### Orange oil (8008-57-9)

|                    |              |
|--------------------|--------------|
| LD50 oral rat      | 4400 mg/kg   |
| LD50 dermal rabbit | > 5000 mg/kg |

### Veltol plus crystals (4940-11-8)

|               |                        |
|---------------|------------------------|
| LD50 oral rat | 1150 mg/kg             |
| LD50 oral     | 1200 mg/kg body weight |

|                                                     |                                                                    |
|-----------------------------------------------------|--------------------------------------------------------------------|
| Skin corrosion/irritation                           | : Not classified                                                   |
| Serious eye damage/irritation                       | : Not classified                                                   |
| Respiratory or skin sensitization                   | : May cause an allergic skin reaction.                             |
| Germ cell mutagenicity                              | : Not classified                                                   |
| Carcinogenicity                                     | : Not classified                                                   |
| Reproductive toxicity                               | : Not classified                                                   |
| STOT-single exposure                                | : Not classified                                                   |
| STOT-repeated exposure                              | : Not classified                                                   |
| Aspiration hazard                                   | : Not classified                                                   |
| Potential Adverse human health effects and symptoms | : Based on available data, the classification criteria are not met |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                                                           |                                                      |
|-----------------------------------------------------------|------------------------------------------------------|
| Ecology - general                                         | : Harmful to aquatic life with long lasting effects. |
| Hazardous to the aquatic environment, short-term (acute)  | : Not classified                                     |
| Hazardous to the aquatic environment, long-term (chronic) | : Harmful to aquatic life with long lasting effects. |

### Benzene carboxaldehyde (100-52-7)

|                 |                                                                                      |
|-----------------|--------------------------------------------------------------------------------------|
| LC50 - Fish [1] | 10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through]) |
|-----------------|--------------------------------------------------------------------------------------|

|                 |                                                                          |
|-----------------|--------------------------------------------------------------------------|
| LC50 - Fish [2] | 12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
|-----------------|--------------------------------------------------------------------------|

### Phenylmethanol (100-51-6)

|                      |                                                                        |
|----------------------|------------------------------------------------------------------------|
| LC50 - Fish [1]      | 460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| LC50 - Fish [2]      | 10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])  |
| EC50 - Crustacea [1] | 23 mg/l (Exposure time: 48 h - Species: water flea)                    |

### Nerol (106-25-2)

|                 |                                                                      |
|-----------------|----------------------------------------------------------------------|
| LC50 - Fish [1] | 20.3 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static]) |
|-----------------|----------------------------------------------------------------------|

### L-Carvone (6485-40-1)

|                 |                                                                             |
|-----------------|-----------------------------------------------------------------------------|
| LC50 - Fish [1] | 6.1 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static]) |
|-----------------|-----------------------------------------------------------------------------|

### Leaf alcohol (928-96-1)

|                 |                                                                                    |
|-----------------|------------------------------------------------------------------------------------|
| LC50 - Fish [1] | 352 – 412 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
|-----------------|------------------------------------------------------------------------------------|

### Trimofix O (144020-22-4)

|                 |                                                                         |
|-----------------|-------------------------------------------------------------------------|
| LC50 - Fish [1] | 0.63 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
|-----------------|-------------------------------------------------------------------------|

### Veltol plus crystals (4940-11-8)

|                 |                                                                |
|-----------------|----------------------------------------------------------------|
| LC50 - Fish [1] | > 85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
|-----------------|----------------------------------------------------------------|

## 12.2. Persistence and degradability

### FRAG0018 Black Cherry Fragrance Oil

|                               |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |
|-------------------------------|------------------|

### Cedarwood oil, Texas (68990-83-0)

|                               |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |
|-------------------------------|------------------|

## 12.3. Bioaccumulative potential

### FRAG0018 Black Cherry Fragrance Oil

|                           |                  |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |
|---------------------------|------------------|

### Benzene carboxaldehyde (100-52-7)

|                                                 |                                  |
|-------------------------------------------------|----------------------------------|
| BCF - Fish [1]                                  | (no significant bioaccumulation) |
| Partition coefficient n-octanol/water (Log Pow) | 1.48 (at 20 °C)                  |

### Phenylmethanol (100-51-6)

|                                                 |     |
|-------------------------------------------------|-----|
| Partition coefficient n-octanol/water (Log Pow) | 1.1 |
|-------------------------------------------------|-----|

### Cedarwood oil, Texas (68990-83-0)

|                           |                  |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |
|---------------------------|------------------|

### Diphenyl oxide (101-84-8)

|                |     |
|----------------|-----|
| BCF - Fish [1] | 470 |
|----------------|-----|

|                                                 |     |
|-------------------------------------------------|-----|
| Partition coefficient n-octanol/water (Log Pow) | 4.2 |
|-------------------------------------------------|-----|

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

|                                            |                                                                                                                                                                    |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Waste treatment methods                    | : Dispose of contents/container in accordance with licensed collector's sorting instructions.                                                                      |
| Product/Packaging disposal recommendations | : Dispose of contents/container in accordance with local/national laws and regulations.<br>Dispose in a safe manner in accordance with local/national regulations. |
| Additional information                     | : Handle empty containers with care because residual vapors are flammable.                                                                                         |
| Ecology - waste materials                  | : Avoid release to the environment.                                                                                                                                |

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

### 14.1 UN number

|               |                  |
|---------------|------------------|
| UN-No. (ADR)  | : Not applicable |
| UN-No. (IMDG) | : Not applicable |
| UN-No. (IATA) | : Not applicable |
| UN-No. (ADN)  | : Not applicable |
| UN-No. (RID)  | : Not applicable |

### 14.2. UN proper shipping name

|                             |                  |
|-----------------------------|------------------|
| Proper Shipping Name (ADR)  | : Not applicable |
| Proper Shipping Name (IMDG) | : Not applicable |
| Proper Shipping Name (IATA) | : Not applicable |
| Proper Shipping Name (ADN)  | : Not applicable |
| Proper Shipping Name (RID)  | : Not applicable |

### 14.3. Transport hazard class(es)

|                                   |                  |
|-----------------------------------|------------------|
| <b>ADR</b>                        |                  |
| Transport hazard class(es) (ADR)  | : Not applicable |
| <b>IMDG</b>                       |                  |
| Transport hazard class(es) (IMDG) | : Not applicable |
| <b>IATA</b>                       |                  |
| Transport hazard class(es) (IATA) | : Not applicable |
| <b>ADN</b>                        |                  |
| Transport hazard class(es) (ADN)  | : Not applicable |
| <b>RID</b>                        |                  |
| Transport hazard class(es) (RID)  | : Not applicable |

### 14.4. Packing group

|                      |                  |
|----------------------|------------------|
| Packing group (ADR)  | : Not applicable |
| Packing group (IMDG) | : Not applicable |

Packing group (IATA) : Not applicable  
Packing group (ADN) : Not applicable  
Packing group (RID) : Not applicable

### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

| Reference code | Applicable                                                                                                                                                                                                                                                    |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 3(b)           | Amyl salicylate ; Benzene carboxaldehyde ; Phenylmethanol ; Cedarwood oil, Texas ; Citronellol Pure ; Damascenone Total ; Geranyl acetate ; Hexyl salicylate ; Iso E Super ; L-Carvone ; Leaf alcohol ; methyl anthranilate ; Nerol ; Orange oil ; Trimofix O |
| 3(c)           | Amyl salicylate ; Cedarwood oil, Texas ; Damascenone Total ; Geranyl acetate ; Hexyl salicylate ; Iso E Super ; Orange oil ; Trimofix O                                                                                                                       |
| 3(a)           | Leaf alcohol ; Orange oil                                                                                                                                                                                                                                     |
| 40.            | Leaf alcohol ; Orange oil                                                                                                                                                                                                                                     |

Contains no REACH candidate substance

Contains no REACH Annex XIV substances.

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance(s) subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

##### France

#### Professional diseases

| Code  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RG 84 | Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide |

##### Germany

Water hazard class (WGK) : WGK 2, significant hazardous to water (Classification according to AwSV, Annex 1)  
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

### Netherlands

SZW-lijst van kankerverwekkende stoffen : Cedarwood oil, Texas ,Orange oil are listed  
 SZW-lijst van mutagene stoffen : Orange oil is listed  
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed  
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed  
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

### Denmark

Class for fire hazard : Class III-1  
 Store unit : 50 liter  
 Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed  
 Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

### Switzerland

Storage class (LK) : LK 10/12 - Liquids

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Other information : None.

### Full text of H- and EUH-phrases:

|                           |                                                                  |
|---------------------------|------------------------------------------------------------------|
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhalation) Category 4                           |
| Acute Tox. 4 (Oral)       | Acute toxicity (oral) Category 4                                 |
| Aquatic Acute 1           | Hazardous to the aquatic environment - Acute Hazard Category 1   |
| Aquatic Chronic 1         | Hazardous to the aquatic environment - Chronic Hazard Category 1 |
| Aquatic Chronic 2         | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Aquatic Chronic 3         | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Asp. Tox. 1               | Aspiration hazard Category 1                                     |
| Eye Irrit. 2              | Serious eye damage/eye irritation, Category 2                    |
| Flam. Liq. 3              | Flammable liquids Category 3                                     |
| Skin Irrit. 2             | Skin corrosion/irritation Category 2                             |
| Skin Sens. 1              | Skin sensitization, Category 1                                   |
| Skin Sens. 1B             | Skin sensitization, Category 1B                                  |
| H226                      | Flammable liquid and vapor.                                      |
| H302                      | Harmful if swallowed.                                            |
| H304                      | May be fatal if swallowed and enters airways.                    |
| H315                      | Causes skin irritation.                                          |
| H317                      | May cause an allergic skin reaction.                             |
| H319                      | Causes serious eye irritation.                                   |
| H332                      | Harmful if inhaled.                                              |
| H400                      | Very toxic to aquatic life.                                      |
| H410                      | Very toxic to aquatic life with long lasting effects.            |
| H411                      | Toxic to aquatic life with long lasting effects.                 |



# FRAG0018 Black Cherry Fragrance Oil

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

|      |                                                    |
|------|----------------------------------------------------|
| H412 | Harmful to aquatic life with long lasting effects. |
|------|----------------------------------------------------|

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.