

# SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended

# CAUSTIC POTASH SOLID (ALL GRADES)

Version 7.0 Print Date 2024/12/09

Revision date / valid from 2024/12/09 MSDS code: MCPF100

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : CAUSTIC POTASH SOLID (ALL GRADES) TSK-DRYI28

Substance name : potassium hydroxide

Index-No. : 019-002-00-8 CAS-No. : 1310-58-3 EC-No. : 215-181-3

EU REACH-Reg. No. : 01-2119487136-33-xxxx

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the : Identified use: See table in front of appendix for a complete

Substance/Mixture overview of identified uses.

Uses advised against : At this moment we have not identified any uses advised

against

Remarks : Before referring to any Exposure Scenario attached to this

Safety Data Sheet please check the grade of the product: the Exposure Scenarios presented are not related to all product

grade

# 1.3. Details of the supplier of the safety data sheet

Company : Supplies for Candles & The Soap Kitchen Ltd

Unit E Swinton Bridge Industrial Estate, White

Lea Road,Swinton South Yorkshire S64 8BH, UK

E-mail address : Office Hours: Mon to Fri 08.00 to 16.00

customerservice@suppliesforcandles.co.uk

1.4. Emergency telephone number TEL: 01709 257151

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to Regulation S.I. 2019/720 (GB CLP)

Regulation S.I. 2019/720 (GB CLP)						
Hazard class	Hazard category	Target Organs	Hazard statements			
Corrosive to metals	Category 1		H290			
Acute toxicity (Oral)	Category 4		H302			
Skin corrosion	Category 1A		H314			
Serious eye damage	Category 1		H318			

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### Most important adverse effects

Human Health : See section 11 for toxicological information.

Physical and chemical

hazards

See section 9/10 for physicochemical information.

Potential environmental

effects

See section 12 for environmental information.

#### 2.2. Label elements

#### Labelling according to Regulation S.I. 2019/720 (GB CLP)

Hazard symbols :





Signal word : Danger

Hazard statements : H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

Precautionary statements

Prevention : P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response : P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do

NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water or shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh

air and keep comfortable for breathing.

Immediately call a POISON

CENTER/doctor.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with

water for several minutes. Remove contact

lenses, if present and easy to do. Continue

rinsing.

P390 Absorb spillage to prevent material

damage.

# Hazardous components which must be listed on the label:

· potassium hydroxide

#### 2.3. Other hazards

The PBT or vPvB criteria of Annex XIII to the REACH Regulation does not apply to inorganic substances.

Ecological information: No information available about endocrine disruption properties for environment.

Toxicological information: No information available about endocrine disruption properties for human health.

Potential for exothermic hazard

# **SECTION 3: Composition/information on ingredients**

# 3.1. Substances

		Classif (Regulation S.I. 20	
Hazardous components	Amount [%]	Hazard class / Hazard category	Hazard statements
potassium hydroxide			
Index-No. : 019-002-00-8 CAS-No. : 1310-58-3 EC-No. : 215-181-3 EU REACH- : 01-2119487136-33-xxxx Reg. No.	<= 100	Met. Corr.1 Acute Tox.4 Oral Skin Corr.1A Eye Dam.1  specific concentration limit Skin Irrit. 2; H315 0.5 - < 2 % Eye Irrit. 2; H319 0.5 - < 2 % Skin Corr. 1A; H314 >= 5 % Skin Corr. 1B; H314 2 - < 5 %  Acute toxicity estimate Acute oral toxicity: 333 mg/kg	H290 H302 H314 H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

General advice : Take off all contaminated clothing immediately.

If inhaled : In case of accident by inhalation: remove casualty to fresh air

and keep at rest. If breathing is irregular or stopped, administer

artificial respiration. Call a physician immediately.

In case of skin contact : Wash off immediately with soap and plenty of water. Call a

physician immediately.

: Rinse immediately with plenty of water, also under the eyelids, In case of eye contact

for at least 15 minutes. Consult an eye specialist immediately.

Go to an ophthalmic hospital if possible.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Never give anything by mouth to an unconscious person. Do

NOT induce vomiting. Call a physician immediately.

Protection of First Aid

Responders

: First Aid responders should pay attention to self-protection and

use the recommended protective clothing.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** : See Section 11 for more detailed information on health effects

and symptoms.

**Effects** : Extremely corrosive and destructive to tissue. If ingested,

> severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach. See Section

11 for more detailed information on health effects and

symptoms.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# SECTION 5: Firefighting measures

# 5.1. Extinguishing media

Suitable extinguishing

media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing High volume water jet

media

# Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Hazardous combustion

products

Incomplete combustion may form toxic pyrolysis products.

The formation of caustic fumes is possible.

### 5.3. Advice for firefighters

Special protective

equipment for firefighters

In the event of fire, wear self-contained breathing

apparatus. Wear appropriate body protection (full protective

suit)

Specific extinguishing

methods

Further advice

: Control smoke with water spray.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

: Keep away unprotected persons. Use personal protective Personal precautions

equipment. Ensure adequate ventilation. Avoid contact with the skin and the eyes. Do not breathe vapours or spray mist.

#### **Environmental precautions**

Environmental precautions

: Do not flush into surface water or sanitary sewer system.

Avoid subsoil penetration.

#### Methods and materials for containment and cleaning up

containment and cleaning

up

Methods and materials for : Use mechanical handling equipment. Keep in suitable, closed

containers for disposal. Flush with plenty of water.

Further information : Treat recovered material as described in the section "Disposal

considerations".

#### Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on personal protective equipment.

See Section 13 for waste treatment information.

# SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

: Keep container tightly closed. Ensure adequate ventilation. Use Advice on safe handling

> personal protective equipment. Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Use respirator with appropriate filter if vapours or aerosol are released. Emergency eye wash fountains and emergency showers should be available in the immediate vicinity.

Hygiene measures : Keep away from food, drink and animal feedingstuffs. Smoking,

eating and drinking should be prohibited in the application area. Wash hands before breaks and at the end of workday. Take off

all contaminated clothing immediately.

# 7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in an area equipped with alkali resistant flooring. Suitable materials for containers: polyethylene containers; Unsuitable

materials for containers: Aluminium; Zinc

Advice on protection against fire and explosion

: The product is not flammable. Gives off hydrogen by reaction

with metals. Risk of explosion.

Further information on storage conditions

: Keep container tightly closed and dry. Product is hygroscopic.

Keep in a well-ventilated place.

Advice on common

storage

: Keep away from food, drink and animal feedingstuffs.

#### 7.3. Specific end use(s)

Specific use(s) : Identified use: See table in front of appendix for a complete

overview of identified uses.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Component: potassium hydroxide CAS-No. 1310-5	8-3
---	-----

#### Derived No Effect Level (DNEL)/Derived Minimal Effect Level (DMEL)

**DNEL** 

Workers, Long-term - local effects, Inhalation : 1 mg/m3

**DNEL** 

Consumers, Long-term - local effects, Inhalation : 1 mg/m3

#### **Predicted No Effect Concentration (PNEC)**

No PNEC value was derived.

# **Other Occupational Exposure Limit Values**

UK. EH40 Workplace Exposure Limits (WELs), as amended, Short Term Exposure Limit

(STEL):

2 mg/m3, (15 minutes)

ELV (IE), Short Term Exposure Limit (STEL):

2 mg/m3, (15 minutes)

### 8.2. Exposure controls

#### Appropriate engineering controls

Refer to protective measures listed in sections 7 and 8.

# Personal protective equipment

Respiratory protection

Advice : In case of brief exposure or low pollution use breathing filter

apparatus.

In case of intensive or longer exposure use self-contained

breathing apparatus.
Recommended Filter type:

Particle filter:P2 Particle filter:P3

Equipment should conform to EN 14387

Hand protection

Advice : The glove material has to be impermeable and resistant to the

product / the substance / the preparation.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace

conditions (mechanical strain, duration of contact).

Protective gloves should be replaced at first signs of wear.

Material : butyl-rubber Break through time : >= 8 h Glove thickness : 0.5 mm

Material : Natural Rubber

Break through time : >= 8 h Glove thickness : 0.5 mm

Material : polychloroprene

Break through time : >= 8 h Glove thickness : 0.5 mm

Material : Nitrile rubber
Break through time : >= 8 h
Glove thickness : 0.35 mm

Material : Fluorinated rubber

Break through time : >= 8 h Glove thickness : 0.4 mm

Material : Polyvinylchloride

Break through time : >= 8 h Glove thickness : 0.5 mm

Eye protection

Advice : Safety goggles

Face-shield

Skin and body protection

Protecting Clothes : Impervious clothing

Chemical resistant apron

**Environmental exposure controls** 

General advice : Do not flush into surface water or sanitary sewer system.

Avoid subsoil penetration.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Form : No data available

Physical state : solid

Colour : white

Odour : odourless

Odour Threshold : Not applicable

Melting point/ range : 360 °C

Boiling point/boiling range : 1,327 °C

Flammability (solid, gas) : does not ignite

Remarks: non-combustible

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower :

flammability limit

Not applicable

Flash point : Not applicable

Auto-ignition temperature : Not applicable

80000000181 / Version 7.0 8/45 EN

Decomposition temperature : No data available

Self-Accelerating

decomposition temperature

(SADT)

No data available

pH : 14 (20 °C)

Concentration: 100 g/l (as aqueous solution)

> 11.5

Concentration: 1 % (as aqueous solution)

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : No data available

Flow time : No data available

Solubility(ies)

Water solubility : 1200 g/l (25 °C)

Solubility in other solvents : No data available

Dissolution Rate : No data available

Partition coefficient: n-

octanol/water

Not applicable

Dispersion Stability : No data available

Vapour pressure : Not applicable

Relative density : No data available

Density : 2.04 g/cm3

Bulk density : No data available

Relative vapour density : Not applicable

Particle characteristics No data available

9.2 Other information

Explosives : Product is not explosive.

Oxidizing properties : not oxidising

Flammability (liquids) : Not applicable

Remarks: non-combustible

Metal corrosion rate : Corrosive to metals

Evaporation rate : Not applicable

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Advice : No decomposition if stored and applied as directed.

Corrosive in contact with metals

10.2. Chemical stability

Advice : Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions : Exothermic reaction with strong bases. Reacts exothermically

with water. Gives off hydrogen by reaction with base metals

(zinc, aluminium). Risk of explosion.

10.4. Conditions to avoid

Conditions to avoid : Protect from humidity and keep away from water. Product is

hygroscopic.

Thermal decomposition : No data available

10.5. Incompatible materials

Materials to avoid : Water, Amines, Ammonia, Light metals, Strong acids,

ammonium compounds, Halogenated compounds, Organic

ΕN

materials

10.6. Hazardous decomposition products

Hazardous decomposition : Sodium oxides, Hydrogen

products

# **SECTION 11: Toxicological information**

# 11.1. Information on the hazard classes within the meaning of Regulation (EC) No. 1272/2008

Component:	ent: potassium hydroxide CAS-No. 1310-5			
	Acute toxicity			
Oral				
LD50 : 333 mg/kg (Rat, male) (OECD Test Guideline 425)				
Inhalation				

Inhalation may cause pain in respiratory system, sneezing, coughing and difficulty in breathing. Risk for pulmonary edema by high concentration.

# **Dermal**

No data available

#### Irritation

#### Skin

Result : Very corrosive (reconstructed human epidermis (RhE)) (OECD

Test Guideline 431) May cause burns with pain, redness and

wounds.

#### Eyes

Result : Very corrosive (Rabbit) (OECD Test Guideline 405)

#### **Sensitisation**

Result : not sensitizing (Guinea pig)

# CMR effects

# **CMR Properties**

Carcinogenicity : No data available

Mutagenicity : In vitro tests did not show mutagenic effects

Teratogenicity : No data available Reproductive toxicity : No data available

#### **Genotoxicity in vitro**

Result : negative (Mutagenicity (Salmonella typhimurium - reverse mutation

assay); with and without metabolic activation)

# **Specific Target Organ Toxicity**

#### Single exposure

Remarks : The substance or mixture is not classified as specific target organ

toxicant, single exposure.

# Repeated exposure

Remarks : The substance or mixture is not classified as specific target organ

80000000181 / Version 7.0 11/45 EN

toxicant, repeated exposure.

# Other toxic properties

#### **Aspiration hazard**

Not applicable,

#### **Further information**

Other relevant toxicity: information

If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

#### 11.2. Information on other hazards

# Data for the product

# **Endocrine disrupting properties**

Assessment

No information available about endocrine disruption properties

for human health.

Component:	potassium hydroxide	CAS-No. 1310-58-3
•		

# **Endocrine disrupting properties**

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

Component:	potassium hydroxide	CAS-No. 1310-58-3			
	Acute toxicity				
	Fish				
LC50	: 80 mg/l (Gambusia affinis (Mosquito	fish); 96 h) (static test)			
LC50	LC50 165 mg/l (Poecilia reticulata; 24 h)				
	Toxicity to daphnia and other aquatic invertebrates				

: No data available

# algae

: No data available

#### **Bacteria**

EC50 : 22 mg/l (Photobacterium phosphoreum; 15 min)

# 12.2. Persistence and degradability

Component:	potassium hydroxide	CAS-No. 1310-58-3			
	Persistence and degradability				
	Persistence				
Result	: No data available				
	Biodegradability				
Result	: The methods for determining the biol	logical degradability are not			

# 12.3. Bioaccumulative potential

Component:	potassium hydroxide	CAS-No. 1310-58-3
	Bioaccumulation	

applicable to inorganic substances.

Result : Bioaccumulation is not expected.

# 12.4. Mobility in soil

Component:	potassium hydroxide	CAS-No. 1310-58-3		
Mobility				

Soil : Adsorption to solid soil phase is not expected.

Water : The product is water soluble.

# 12.5. Results of PBT and vPvB assessment

80000000181 / Version 7.0 13/45 EN

# Data for the product

#### Results of PBT and vPvB assessment

Result : The PBT or vPvB criteria of Annex XIII to the REACH Regulation

does not apply to inorganic substances.

Component: potassium hydroxide CAS-No. 1310-58-3

Results of PBT and vPvB assessment

Result : The PBT or vPvB criteria of Annex XIII to the REACH Regulation

does not apply to inorganic substances.

# 12.6. Endocrine disrupting properties

# Data for the product

Endocrine disrupting potential

No information available about endocrine disruption properties for

environment.

Component: potassium hydroxide CAS-No. 1310-58-3

Endocrine disrupting potential

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# 12.7. Other adverse effects

Data for the product					
	Additional ecological information	1			
Result : Do not flush into surface water or sanitary sewer system.  Avoid subsoil penetration.  Harmful effects to aquatic organisms due to pH-shift.					
Component:	potassium hydroxide CAS-No. 1310-58-3				
	Additional ecological information				
Result	: Do not flush into surface water or sa Harmful effects to aquatic organism				

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product : Disposal together with normal waste is not allowed. Special

disposal required according to local regulations. Do not let product enter drains. Contact waste disposal services. This

80000000181 / Version 7.0 14/45 EN

product shall be disposed of or recovered in compliance with Directive 2008/98/EC on waste as lastly amended.

Contaminated packaging : Empty contaminated packagings thoroughly. They can be

recycled after thorough and proper cleaning. If recycling is not practicable, dispose of in compliance with local regulations.

European Waste Catalogue Number

No waste code according to the European Waste Catalogue can be assigned for this product, as the intended use dictates the assignment. The waste code is established in consultation

with the regional waste disposer.

# **SECTION 14: Transport information**

#### 14.1. UN number or ID number

1813

# 14.2. UN proper shipping name

ADR : POTASSIUM HYDROXIDE, SOLID RID : POTASSIUM HYDROXIDE, SOLID IMDG : POTASSIUM HYDROXIDE, SOLID

# 14.3. Transport hazard class(es)

ADR-Class : 8

(Labels; Classification Code; Hazard 8; C6; 80; (E)

Identification Number; Tunnel restriction

code)

RID-Class : 8

(Labels; Classification Code; Hazard 8; C6; 80

Identification Number)

IMDG-Class : 8

(Labels; EmS) 8; F-A, S-B

#### 14.4. Packaging group

ADR : II

RID : II

IMDG : II

#### 14.5. Environmental hazards

Environmentally hazardous according to ADR : no Environmentally hazardous according to RID : no Marine Pollutant according to IMDG-Code : no

#### 14.6. Special precautions for user

Not applicable.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# Data for the product

Other regulations SDS updated according to Regulation (EU) 2020/878

#### Component: potassium hydroxide CAS-No. 1310-58-3

**Rotterdam Convention** on the Prior Informed Consent (PIC) Procedure for Certain Hazardous Chemicals and Pesticides in International Trade

; The substance/mixture does not fall under this legislation.

EU. REACH, Annex XVII, : Point Nos.: , 75; Listed Marketing and Use Restrictions (Regulation 1907/2006/EC)

EU. Regulation No. 1223/2009 on cosmetic products, Annex III: List of Restricted Substances in Cosmetic Products

Maximum concentration in ready for use preparation: 4.5 %; Professional use products for straightening hair; See the text of the regulation for applicable exceptions or provisions.

Maximum concentration in ready for use preparation: 2 %; General use products for straightening hair; See the text of the regulation for applicable exceptions or provisions.

Maximum concentration in ready for use preparation: 5 %; Nail cuticle products; See the text of the regulation for applicable exceptions or provisions.

- ; Cosmetic products other than depilatories; See the text of the regulation for applicable exceptions or provisions.
- ; Depilatories; See the text of the regulation for applicable exceptions or provisions.

EU. Directive : ; The substance/mixture does not fall under this legislation.

2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances,

Annex I

Germany. List of : WGK 1: slightly hazardous to water: 345

Substances That Are Not Water-Endangering, AwSV of 21 April 2017, UBA, Banz AT, as amended

#### 15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

#### **SECTION 16: Other information**

#### Full text of H-Statements referred to under sections 2 and 3.

H290 May be corrosive to metals. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

#### Full text of the Notes referred to under section 3.

#### **Abbreviations and Acronyms**

AU AIICL Australia. Industrial Chemicals Act (AIIC) List

**BCF** bioconcentration factor

BOD biochemical oxygen demand
CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

CMR carcinogenic, mutagenic or toxic to reproduction

COD chemical oxygen demand DNEL derived no-effect level

DSL Canada. Environmental Protection Act, Domestic Substances List EINECS European Inventory of Existing Commercial Chemical Substances

**ELINCS** European List of Notified Chemical Substances

ENCS (JP) Japan. Kashin-Hou Law List

GHS Globally Harmonized System of Classification and Labelling of

Chemicals

IECSC China. Inventory of Existing Chemical Substances
INSQ Mexico. National Inventory of Chemical Substances

ISHL (JP) Japan. Inventory of Industrial Safety & Health

**KECI (KR)** Korea. Existing Chemicals Inventory

**LC50** median lethal concentration

**LOAEC** lowest observed adverse effect concentration

LOAEL lowest observed adverse effect level

**LOEL** lowest observed effect level

NDSL Canada. Environmental Protection Act. Non-Domestic Substances

List

**NLP** no-longer polymer

NOAEC no observed adverse effect concentration

NOAEL no observed adverse effect level NOEC no observed effect concentration

NOEL no observed effect level

**NZIOC** New Zealand. Inventory of Chemicals

OECD Organisation for Economic Cooperation and Development

OEL occupational exposure limit
ONT INV Canada. Ontario Inventory List
PBT persistent, bioaccumulative and toxic

PHARM (JP) Japan. Pharmacopoeia Listing

PICCS (PH) Philippines. Inventory of Chemicals and Chemical Substances

PNEC predicted no-effect concentration
REACH Auth. No.: REACH Authorisation Number

**REACH AuthAppC. No.** REACH Authorisation Application Consultation Number

**UK REACH Auth. No.:** UK REACH Authorisation Number

**UK REACH AuthAppC.** 

No.

UK REACH Authorisation Application Consultation Number

UK REACH-Reg.No
UK REACH Registration Number
specific target organ toxicity
substance of very high concern
TCSI
Taiwan. Existing Chemicals Inventory

**TH INV** Thailand. Existing Chemicals Inventory from FDA

TSCA US. Toxic Substances Control Act

**UVCB** substance of unknown or variable composition, complex reaction

products or biological materials

VN INVL Vietnam. National Chemical Inventory vPvB very persistent and very bioaccumulative

**Further information** 

Key literature references : Supplier information and data from the "Database of registered

and sources for data

substances" of the European Chemicals Agency (ECHA) were

used to create this safety data sheet.

Methods used for product classification

The classification for human health, physical and chemical hazards and environmental hazards were derived from a combination of calculation methods and if available test data.

Hints for trainings

The workers have to be trained regularly on the safe handling of the products based on the information provided in the Safety Data Sheet and the local conditions of the workplace. National regulations for the training of workers in the handling of

hazardous materials must be adhered to.

Other information

The information provided in this Safety Data Sheet is correct to our knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements and is not to be considered as a warranty or quality specification and does not constitute a legal relationship.

The information contained in this Safety Data Sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

|| Indicates updated section.

No.	Short title	REACH Auth. No.:/ REACH AuthAppC. No.	Main User Group (SU)	Sector of Use (SU)	Product Category (PC)	Process Category (PROC)	Environme ntal Release Category (ERC)	Article Category (AC)	Specified
1	Manufacture of substance - liquid	NA NA	3	NA	NA	1, 2, 3, 8a, 8b, 9	1	NA	ES50
2	Manufacture of substance - solid	NA NA	3	NA	NA	1, 2, 3, 4, 8a, 8b, 9	1	NA	ES53
3	Other consumer uses	NA NA	21	NA	20	NA	9a, 9b	3	ES62
4	Industrial use	NA NA	3	NA	NA	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 12, 13, 14, 15, 19, 20	1, 2, 3, 4, 5, 6a, 6b, 6c, 6d, 7	NA	ES55
5	Professional use	NA NA	22	NA	NA	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 11, 13, 14, 15, 19, 20	8a, 8b, 8c, 8d, 8e, 8f, 9a, 9b, 10a, 10b, 11a, 11b	NA	ES58
6	Consumer use	NA NA	21	NA	9a, 35	NA	8a, 8b, 8d, 8e, 9a	NA	ES60

1. Short title of Exposure Scenario 1: Manufacture of substance - liquid				
Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites			
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)			
Environmental Release Categories	ERC1: Manufacture of subs	stances		
2.1 Contributing scenario co	ntrolling environmental	exposure for: ERC1		
	Concentration of the Substance in Mixture/Article Concentration of the Substance in	Covers the percentage of the substance in the product up to 100 % (unless stated differently).  The substance is used up in the process,		
Product characteristics	Mixture/Article  Concentration of the Substance in Mixture/Article	Concentration of substance in product: 50%  Product may be diluted before use, Concentration of substance in product: > 10%, Covers percentage of substance in the product up to 75%.		
	Physical Form (at time of use)	liquid		
Fraguency and duration of use	Continuous exposure	200 days/year, Continuous release, Batch process		
Frequency and duration of use	Continuous exposure	8 hours/day, Continuous release, Batch process		
Technical conditions and measures at process level to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Water	Neutralization is normally necessary before waste water is discharged into water treatment plants., Regular control of the pH value during introduction into open waters is required., In general discharges should be carried out such that pH changes in receiving surface waters are minimised., In general most aquatic organisms can tolerate pH values in the range of 6-9. This is also reflected in the description of standard OECD tests with aquatic organisms., Risk management measures related to the environment aim to avoid discharging the substance into municipal wastewater or to surface water, in case such discharges are expected to cause significant pH changes., Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.		
0 19	Type of Sewage Treatment Plant	WWTP/local STP (e.g. biological treatment)		
Conditions and measures related to sewage treatment plant	Sludge Treatment	pH adjustment		
	The pH of wastewater released from manufacturing sites should be between 6 and 9.			
Conditions and measures related to external treatment of waste for	I waste treatment I Solutions with blob be-value must be belitralized			
800000000181 / Version 7.0	21/45	EN		

CAUSTIC POTASH S	OLID (ALL GRAL	DES)
disposal		before discharge.
	Disposal methods	Waste should be reused or discharged to the industrial wastewater and further neutralized if needed.
	Contain and dispose of wa according to local regulation	ste in accordance with environmental legislation and ons.
2.2 Contributing scenario co PROC8b, PROC9	ntrolling worker exposu	re for: PROC1, PROC2, PROC3, PROC8a,
	Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Duadwat ahaya ta riation	Concentration of the Substance in Mixture/Article	The substance is used up in the process, Concentration of substance in product : 50%
Product characteristics	Concentration of the Substance in Mixture/Article	Product may be diluted before use, Concentration of substance in product: > 10%, Covers percentage of substance in the product up to 75%.
	Physical Form (at time of use)	liquid
	Assumes use at not more	than 20°C above ambient temperature.
Amount used	The amount used per work	er varies from activity to activity
	Frequency of use	200 days/year
Frequency and duration of use	Covers daily exposures up	to 8 hours
	Frequency of use	<= 8 h/day
Technical conditions and measures to control dispersion from source towards the worker	Use in closed, continuous process with occasional controlled exposure Use in batch and other process (synthesis) where opportunity for exposure arises	Use closed systems or covering of open containers (e.g. screens)  Transport over pipes, technical barrel filling/emptying of barrel with automatic systems (suction pumps etc.)  Use of pliers, grip arms with long handles with manual use to avoid direct contact and exposure by splashes (no working over one's head)  Use in closed process, no likelihood of exposure Automate activity where possible.  Local exhaust ventilation is not required but is recommended where exposure arises Avoid splashing.  Provide a good standard of general ventilation.  Natural ventilation is from doors, windows etc.  Controlled ventilation means air is supplied or removed by a powered fan.  Prevent further leakage or spillage if safe to do so.
Organisational measures to prevent /limit releases, dispersion and exposure	General exposures	Workers in the risky process/areas identified should be trained a) to avoid to work without respiratory protection and b) to understand the corrosive properties and, especially, the respiratory inhalation effects and c) to follow the safety procedures instructed by the employer.  The employer has also to ascertain that the required PPE is available  Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment.

		prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.  Ensure control measures are regularly inspected and maintained.  The work place and work methods shall be organized in such a way that direct contact with the product is prevented or minimized.  Supervision in place to check that the RMMs in place are being used correctly and OC's followed
Conditions and measures related to personal protection, hygiene and health evaluation	General exposures	Avoid contact with skin.  Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves, boots and protective coverall)  In case of dust or aerosol formation: use respiratory protection with approved filter (P2) material: nitrile-rubber, fluorinated rubber, material thickness: 0.35-0.4 mm, breakthrough time: > 480 min  Chemical resistant goggles must be worn.  If splashes are likely to occur: wear tightly fitting safety goggles, face—shield Rubber or plastic boots  Avoid direct eye contact with product, also via contamination on hands.
	-	s tested to EN374. (Efficiency: 95 %)
	Wear alkali-resistant protective clothing. (Efficiency: 95 %)	

#### 3. Exposure estimation and reference to its source

#### **Environment**

**ERC1: ECETOC TRA** 

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC1	liquid	Water	All routes		< 1
ERC1	liquid	Indirect exposure to humans via the environment	man via environment		<1

This substance is corrosive. The environmental exposure assessment is only relevant for the aquatic environment, when applicable including STPs/WWTP's, as emissions in the industrial stages mainly apply to (waste) water. The aquatic effect and risk assessment only deals with the effect on organisms/ecosystems due to possible pH changes related to OH- discharges, as the toxicity of the metal ion is expected to be insignificant compared to the (potential) pH effect. The sludge application route is not relevant for the emission to agricultural soil, as no sorption of the substance to particulate matter will occur in STPs/WWTPs. If emitted to air as a water-based aerosol, the substance will be rapidly neutralised as a result of its reaction with CO2 (or acids). Significant emissions to air are not expected due to the very low vapour pressure of the substance. If emitted to soil, sorption to soil particles will be negligible. Significant emissions to the terrestrial environment are not expected. The sediment compartment is not considered, because it is not relevant for the substance. Qualitative risk characterisation. The environmental release is considered negligible Qualitative approach to the determination of safe use. Any pH effect of local releases will be neutralized by the buffer capacity of the receiving water and therefore no pH impacts at the regional scale related to KOH releases should be expected.

#### Workers

Relevant for all PROCs: ECETOC TRA worker v3

PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC9, Relevant for all PROCs: Other measured data

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
Relevant for all PROCs	worst-case	Worker - inhalation, local, acute	0.33mg/m³	< 1
Relevant for all PROCs	worst-case	Worker - inhalative, long- term - local	0.33mg/m³	< 1
Relevant for all PROCs	General exposures	Inhalation worker exposure	0.14mg/m³	
Relevant for all PROCs, PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC9	All relevant routes of exposure	Worker - inhalative, long- term - local	0.56mg/m³	0.56
PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC9	All relevant routes of exposure	Worker - dermal, long- term - local		<1
Relevant for all PROCs		Inhalation worker exposure	0.17mg/m³	

Indirect exposure of humans via the environment is not relevant in the case of this substance. Estimated dermal exposure value is regarded to be negligible. This substance is corrosive. The substance is not expected to be systemically available in the body under normal handling and use conditions. The environmental release is considered negligible Qualitative approach to the determination of safe use. Qualitative approach used to conclude safe use. Significant emissions to air are not expected due to the very low vapour pressure of the substance. Safe use for exposures >4 h. Also without the use of LEV or personal breathing protection.

# 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Health

Important note: By demonstrating a safe use when comparing exposure estimates with the long-term DNEL, the acute DNEL is therefore also covered (according to R.14 guidance, acute exposure levels can be derived by multiplying long-term exposure estimates by a factor of 2).

Worker exposure was modeled following worst case scenario, any deviation should be checked using ECETOC TRA tool

If measured data are not available, the DU may make use of an appropriate scaling tool such as ECETOC TRA. For further information on the assessment method, see: https://www.ecetoc.org/

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

According to the NaOH EU RAR (2007), dermal exposure to >2% KOH formulations is not quantitatively assessed.

#### Environment

If the local conditions deviate significantly from the values in the EU RAR, then further site specific evaluation is required

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Measured data could be used to confirm exposure levels are within the boundaries of the exposure scenario. The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

# CAUSTIC POTASH SOLID (ALL GRADES) For further information on the assessment method, see: https://www.ecetoc.org/ Additional good practice advice beyond the REACH Chemical Safety Assessment Local exhaust ventilation is not required but good practice. Assumes a good basic standard of occupational hygiene is implemented. Replacing, where appropriated, manual processes by automated and/or closed processes. This would avoid irritating mists, sprayings and subsequent potential splashes. General ventilation is good practice unless local exhaust ventilation Training staff on good practice 80000000181 / Version 7.0 25/45 ΕN

1. Short title of Exposure Scenario 2: Manufacture of substance - solid				
Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites			
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)			
Environmental Release Categories	ERC1: Manufacture of sub	stances		
2.1 Contributing scenario co	ntrolling environmental	exposure for: ERC1		
	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 90%., Commercial solid product contains in general 10% of water.		
Product characteristics	Physical Form (at time of use)	Solid, low dustiness		
	At ambient temperature the chemical is a solid and the vapour pressure is therefore very low			
Frequency and duration of use	Continuous exposure	200 days/year, The maximum duration considered for this exposure scenario is a full working shift: 8 hrs/day (40 hours/week).		
Technical conditions and measures at process level to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Water	Regular control of the pH value during introduction into open waters is required., In general discharges should be carried out such that pH changes in receiving surface waters are minimised., In general most aquatic organisms can tolerate pH values in the range of 6-9. This is also reflected in the description of standard OECD tests with aquatic organisms., Risk management measures related to the environment aim to avoid discharging the substance into municipal wastewater or to surface water, in case such discharges are expected to cause significant pH changes., Neutralization is normally necessary before waste water is discharged into water treatment plants., Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system. (waste:, Liquid preparations ERC1)		
Conditions and management related	Type of Sewage Treatment Plant	WWTP/local STP (e.g. biological treatment)		
Conditions and measures related to sewage treatment plant		pH adjustment assed from manufacturing sites should be between 6		
Conditions and measures related to external treatment of waste for	and 9.  Waste treatment	Solutions with high pH-value must be neutralized before discharge.		
disposal	Disposal methods	Waste should be reused or discharged to the		
80000000181 / Version 7.0 26/45 EN				

CAUSTIC POTASH S	OLID (ALL	GRAD	ES)
			induct

industrial wastewater and further neutralized if needed.

Contain and dispose of waste in accordance with environmental legislation and according to local regulations.

# 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9

PROC8a, PROC8b, PROC	PROC8a, PROC8b, PROC9			
	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.		
Product characteristics	Concentration of the Substance in Mixture/Article	The substance is used up in the process, Concentration of substance in product : 50%		
	Concentration of the Substance in Mixture/Article	Product may be diluted before use, Concentration of substance in product: > 10%, Covers percentage of substance in the product up to 75%.		
	Physical Form (at time of use)	Solid, low dustiness		
Amount used	Amount per Day	21000 kg		
Amount used	The amount used per work	er varies from activity to activity		
	Frequency of use	200 days/year		
Frequency and duration of use	Covers daily exposures up	to 8 hours		
	Frequency of use	5 days/week		
Other operational conditions	Indoor use			
affecting workers exposure	Assumes use at not more t	han 20°C above ambient temperature.		
Technical conditions and measures to control dispersion from source towards the worker	Use in closed, continuous process with occasional controlled exposure Use in batch and other process (synthesis) where opportunity for exposure arises	Use closed systems or covering of open containers (e.g. screens)  Transport over pipes, technical barrel filling/emptying of barrel with automatic systems (suction pumps etc.)  Use of pliers, grip arms with long handles with manual use to avoid direct contact and exposure by splashes (no working over one's head)  Use in closed process, no likelihood of exposure Automate activity where possible.  Local exhaust ventilation is not required but is recommended where exposure arises  Avoid splashing.  Provide a good standard of general ventilation.  Natural ventilation is from doors, windows etc.  Controlled ventilation means air is supplied or removed by a powered fan.		
Organisational measures to prevent /limit releases, dispersion and exposure	General exposures	Workers in the risky process/areas identified should be trained a) to avoid to work without respiratory protection and b) to understand the corrosive properties and, especially, the respiratory inhalation effects and c) to follow the safety procedures instructed by the employer.  The employer has also to ascertain that the required PPE is available Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment.  Drain down and flush equipment where possible prior to maintenance. Where there is potential for		
800000000181 / Version 7.0	27/45	EN		

		exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.  Ensure control measures are regularly inspected and maintained.  The work place and work methods shall be organized in such a way that direct contact with the product is prevented or minimized.  Supervision in place to check that the RMMs in place are being used correctly and OC's followed
Conditions and measures related to personal protection, hygiene and health evaluation	General exposures	Avoid contact with skin.  Workers wear protective clothing (face/eye protection, helmet, anti-acid gloves, boots and protective coverall)  In case of dust or aerosol formation: use respiratory protection with approved filter (P2) material: nitrile-rubber, fluorinated rubber, material thickness: 0.35-0.4 mm, breakthrough time: > 480 min  Chemical resistant goggles must be worn.  If splashes are likely to occur: wear tightly fitting safety goggles, face—shield Rubber or plastic boots  Avoid direct eye contact with product, also via contamination on hands.

# 3. Exposure estimation and reference to its source

#### **Environment**

Significant emissions to air are not expected due to the very low vapour pressure of the substance. Significant emissions to the terrestrial environment are not expected. If emitted to air as a water-based aerosol, the substance will be rapidly neutralised as a result of its reaction with CO2 (or acids). The sediment compartment is not considered, because it is not relevant for the substance. This substance is corrosive. The environmental exposure assessment is only relevant for the aquatic environment, when applicable including STPs/WWTP's, as emissions in the industrial stages mainly apply to (waste) water. The aquatic effect and risk assessment only deals with the effect on organisms/ecosystems due to possible pH changes related to OH- discharges, as the toxicity of the metal ion is expected to be insignificant compared to the (potential) pH effect. Qualitative risk characterisation. The sludge application route is not relevant for the emission to agricultural soil, as no sorption of the substance to particulate matter will occur in STPs/WWTPs.

#### Workers

PROC1, PROC2, PROC3, PROC4, PROC8a, PROC9, Relevant for all PROCs: ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1, PROC2		Inhalation worker exposure	0.01mg/m3	
PROC3, PROC9		Inhalation worker exposure	0.1mg/m3	< 1
PROC4, PROC8a		Inhalation worker exposure	0.5mg/m3	< 1
Relevant for all		Worker inhalation, acute	0.2mg/m3	0.2

CAUSTIC		ALL CRADES		
CAUSTIC	CAUSTIC POTASH SOLID (ALL GRADES)			
PROCs		and long-term - local and		
		systemic		
Indirect exposure	e of humans via the environm	nent is not relevant in the cas	e of this substance.	

# 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Health

Worker exposure was modeled following worst case scenario, any deviation should be checked using ECETOC TRA tool

If measured data are not available, the DU may make use of an appropriate scaling tool such as ECETOC TRA. Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Inhalation Exposure is estimated with Ecetoc TRA

Environment

If the local conditions deviate significantly from the values in the EU RAR, then further site specific evaluation is required

Measured data could be used to confirm exposure levels are within the boundaries of the exposure scenario. The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

For further information on the assessment method, see: https://www.ecetoc.org/

If measured data are not available, the DU may make use of an appropriate scaling tool such as ECETOC TRA. Important note: By demonstrating a safe use when comparing exposure estimates with the long-term DNEL, the acute DNEL is therefore also covered (according to R.14 guidance, acute exposure levels can be derived by multiplying long-term exposure estimates by a factor of 2).

Inhalation Exposure is estimated with Ecetoc TRA

For further information on the assessment method, see: https://www.ecetoc.org/

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

# Additional good practice advice beyond the REACH Chemical Safety Assessment

Local exhaust ventilation is not required but good practice.

General ventilation is good practice unless local exhaust ventilation

Assumes a good basic standard of occupational hygiene is implemented.

CAUSTIC POTASH SOLID (ALL GRADES)
-----------------------------------

1. Short title of Exposure Scenario 3: Other consumer uses				
Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)			
Chemical product category	PC20: Products such as plagents	H-regulators, flocculants, precipitants, neutralization		
Article categories	AC3: Electrical batteries an	nd accumulators		
Environmental Release Categories		door use of substances in closed systems utdoor use of substances in closed systems		
2.1 Contributing scenario co	ntrolling environmental	exposure for: ERC9a, ERC9b		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 0,5%		
	Physical Form (at time of use)	liquid		
Technical conditions and measures at process level to	There are no specific risk n	nanagement measures related to environment.		
prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site				
Conditions and measures related to external treatment of waste for disposal	Disposal methods	Batteries should be recycled as much as possible (e.g. by returning to a public recycling facility)., Recovery of the substance from alkaline batteries includes emptying the electrolyte, collection and neutralization.		
2.2 Contributing scenario co	ntrolling consumer expo	osure for: PC20, AC3		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 0,5%		
Trouble sharacteriones	Physical Form (at time of use)	liquid		
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	For use in batteries, it is required to use completely sealed articles with a long service life maintenance. Keep away from children. It is required that improved use instructions, and product information should always be provided to the consumers. This clearly can efficiently reduce the risk of misuse.		
	Exposure to the substance is considered to occur only accidentally if the required protection is strictly adhered to			

# 3. Exposure estimation and reference to its source

# **Environment**

ERC9a: ECETOC TRA

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC9a					< 1
ERC9a		Indirect exposure			< 1

CALISTIC POTASH S	SOLID (ALL GRADES)	
CAUSTIC PUTASIT	SOLID (ALL GRADES)	
	to humans via the environment	
There is no environmental releas	e as batteries are sealed articles with a lo	ong service life. Exposure is considered

negligible. The environmental exposure has been evaluated on the basis of the EU RAR. no exposure expected.

#### **Consumers**

PC20: ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PC20		Consumer - inhalative, long-term - local		< 1
PC20		Consumer - dermal, long- term - local		< 1

Consumer exposure to the substance in batteries is zero because batteries are sealed articles with a long service life maintenance. This substance is corrosive. Qualitative assessment.

# 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Health

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

A quantitative risk assessment is not required for human health.

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Measured data could be used to confirm exposure levels are within the boundaries of the exposure scenario. The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

#### Additional good practice advice beyond the REACH Chemical Safety Assessment

General good hygiene and housekeeping.

1. Short title of Exposure Scenario 4: Industrial use					
Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites				
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact) PROC7: Industrial spraying PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC10: Use of blowing agents in manufacture of foam PROC13: Treatment of articles by dipping and pouring PROC14: Production of preparations or articles by tabletting, compression, extrusion, pelletisation PROC15: Use as laboratory reagent PROC19: Hand-mixing with intimate contact and only PPE available PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems				
Environmental Release Categories	ERC1: Manufacture of substances ERC2: Formulation of preparations ERC3: Formulation in materials ERC4: Industrial use of processing aids in processes and products, not becoming part of articles ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates) ERC6b: Industrial use of reactive processing aids ERC6c: Industrial use of monomers for manufacture of thermoplastics ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers				
ERC7: Industrial use of substances in closed systems  2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7					
Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.			
	Physical Form (at time of use)	liquid, Solid, low dustiness			
Frequency and duration of use	Continuous exposure	200 days/year, Continuous release			
-	Continuous exposure	8 hours/day, Continuous release			
Technical conditions and measures at process level to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and	Water	Neutralization is normally necessary before waste water is discharged into water treatment plants., Regular control of the pH value during introduction into open waters is required., In general discharges should be carried out such that pH changes in			
800000000181 / Version 7.0					

CAUSTIC POTASH S	OLID (ALL GRAD	DES)
releases to soil Organizational measures to prevent/limit release from the site		receiving surface waters are minimised., In general most aquatic organisms can tolerate pH values in the range of 6-9. This is also reflected in the description of standard OECD tests with aquatic organisms., Risk management measures related to the environment aim to avoid discharging the substance into municipal wastewater or to surface water, in case such discharges are expected to cause significant pH changes., Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system., Drift should be minimized
	Comply with all local legisla	ative requirements on permitted local emission limits.
	Type of Sewage Treatment Plant	WWTP/local STP (e.g. biological treatment)
Conditions and measures related to sewage treatment plant	Sludge Treatment	pH adjustment
	The pH of wastewater released and 9.	ased from manufacturing sites should be between 6
Conditions and measures related to external treatment of waste for disposal	Waste treatment	Solutions with high pH-value must be neutralized before discharge.
	Disposal methods	Waste should be reused or discharged to the industrial wastewater and further neutralized if needed., This material and its container must be disposed of in a safe way (e.g. by returning to a public recycling facility)., If container is empty, trash as regular municipal waste.
	Contain and dispose of wa according to local regulation	ste in accordance with environmental legislation and ns.
		re for: PROC1, PROC2, PROC3, PROC4, C10, PROC12, PROC13, PROC14, PROC15,
The process categories mention categories could also be possil		to be the most important ones but other process
Product characteristics	Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	solid, liquid
Amount used	The amount used per work	er varies from activity to activity
	Covers daily exposures up	to 8 hours, Continuous use/release
Frequency and duration of use	Frequency of use	200 days/year(Industrial use )
Trequency and daration or doc	Covers daily exposures up	
Other energianal and 199	Frequency of use	< 15 minutes/day(Liquid preparations )
Other operational conditions affecting workers exposure	Indoor or outdoor use	
Technical conditions and measures to control dispersion from source towards the worker	General exposures	Use closed systems or covering of open containers (e.g. screens) Use of pliers, grip arms with long handles with manual use to avoid direct contact and exposure by splashes (no working over one's head) Transport over pipes, technical barrel filling/emptying of barrel with automatic systems (suction pumps etc.) Automate activity where possible.

CAUSTIC POTASH S	OLID (ALL GRA	DES)
		Transfer via enclosed lines. Ensure material transfers are under containment or extract ventilation. Avoid splashing. Containment of liquid volumes in sumps to collect/prevent accidental spillage Provide local exhaust ventilation (LEV). or Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Organisational measures to prevent /limit releases, dispersion and exposure	General exposures	Workers in the risky process/areas identified should be trained a) to avoid to work without respiratory protection and b) to understand the corrosive properties and, especially, the respiratory inhalation effects and c) to follow the safety procedures instructed by the employer.  The employer has also to ascertain that the required PPE is available Replacing, where appropriated, manual processes by automated and/or closed processes. This would avoid irritating mists, sprayings and subsequent potential splashes.  Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment.  Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.  Ensure control measures are regularly inspected and maintained.  Supervision in place to check that the RMMs in place are being used correctly and OC's followed
Conditions and measures related to personal protection, hygiene and health evaluation	General exposures	In case of dust or aerosol formation: use respiratory protection with approved filter (P2) Use eye protection according to EN 166. Wear chemically resistant gloves. Wear suitable gloves tested to EN374. material: butyl-rubber, PVC, polychloroprene with natural latex liner, material thickness: 0.5 mm, breakthrough time: >480 min material: nitrile-rubber, fluorinated rubber, material thickness: 0.35-0.4 mm, breakthrough time: > 480 min If splashes are likely to occur: Wear suitable protective clothing, aprons, shield and suits Wear rubber boots. Tightly fitting safety goggles

	Face-shield
General exposures	Dermal Protection Wear suitable gloves tested to EN374. Wear alkali-resistant protective clothing. (Efficiency: 95 %)

Worker can be exposed to corrosive concentrations

#### 3. Exposure estimation and reference to its source

#### **Environment**

Relevant for all ERCs: ECETOC TRA model v2 ERC1. ERC2. ERC4. ERC6a. ERC6b: ECETOC TRA

21.01, 21.02, 21.01, 21.000, 202100 11.1					
Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
Relevant for all ERCs					< 1
ERC1, ERC2, ERC4, ERC6a, ERC6b	liquid	Indirect exposure to humans via the environment			< 1

Substance will disassociate upon contact with water, the only effect is the pH effect, therefore after passing through the STP exposure is considered negligible and with no risk. Bioaccumulation will not occur. Significant emissions to air are not expected due to the very low vapour pressure of the substance. Significant emissions to the terrestrial environment are not expected. If emitted to air as a water-based aerosol, the substance will be rapidly neutralised as a result of its reaction with CO2 (or acids). The sediment compartment is not considered, because it is not relevant for the substance. This substance is corrosive. The environmental exposure assessment is only relevant for the aquatic environment, when applicable including STPs/WWTP's, as emissions in the industrial stages mainly apply to (waste) water. The aquatic effect and risk assessment only deals with the effect on organisms/ecosystems due to possible pH changes related to OH- discharges, as the toxicity of the metal ion is expected to be insignificant compared to the (potential) pH effect. Qualitative risk characterisation. The sludge application route is not relevant for the emission to agricultural soil, as no sorption of the substance to particulate matter will occur in STPs/WWTPs.

#### Workers

PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC15, PROC19: ECETOC TRA worker v3

PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC15, PROC19: MEASE 1.02

PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC15; Inhalation exposure

PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC19, Relevant for all PROCs: ECETOC TRA

# 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Health

Important note: By demonstrating a safe use when comparing exposure estimates with the long-term DNEL, the acute DNEL is therefore also covered (according to R.14 guidance, acute exposure levels can be derived by multiplying long-term exposure estimates by a factor of 2).

Worker exposure was modeled following worst case scenario, any deviation should be checked using ECETOC TRA tool

If measured data are not available, the DU may make use of an appropriate scaling tool such as ECETOC TRA. For further information on the assessment method, see: https://www.ecetoc.org/

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Environment

If the local conditions deviate significantly from the values in the EU RAR, then further site specific evaluation is required

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Measured data could be used to confirm exposure levels are within the boundaries of the exposure scenario. The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

For further information on the assessment method, see: https://www.ecetoc.org/

Guidance is based on assumed operating conditions which may not be applicable to all sites. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

DU's can calculate their own Risk Ratios and/or PEC/PNEC ratios using DNEL's and PNEC's listed in the SDS, as well as the actual quantities of the substance, daily usage pattern, substance concentration, etc. Does not present any particular risk for environment.

#### Additional good practice advice beyond the REACH Chemical Safety Assessment

In line with the requirements of good agricultural practice, agricultural soil should be assessed prior to application of the substance and the application rate should be adjusted according to the results of the assessment and crop requirements.

Local exhaust ventilation is not required but good practice.

General ventilation is good practice unless local exhaust ventilation

Assumes a good basic standard of occupational hygiene is implemented.

To improve air quality and avoid potential respiratory track irritation in working areas.

1. Short title of Exposure Scenario 5: Professional use				
Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)			
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact) PROC7: Industrial spraying PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC11: Non industrial spraying PROC13: Treatment of articles by dipping and pouring PROC14: Production of preparations or articles by tabletting, compression, extrusion, pelletisation PROC15: Use as laboratory reagent PROC19: Hand-mixing with intimate contact and only PPE available PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems			
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8b: Wide dispersive indoor use of reactive substances in open systems ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix ERC8d: Wide dispersive outdoor use of processing aids in open systems ERC8e: Wide dispersive outdoor use of reactive substances in open systems ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems ERC10a: Wide dispersive outdoor use of long-life articles and materials with low release ERC10b: Wide dispersive outdoor use of long-life articles and materials with high or intended release (including abrasive processing) ERC11a: Wide dispersive indoor use of long-life articles and materials with low release ERC11b: Wide dispersive indoor use of long-life articles and materials with high or intended release (including abrasive processing)			
ERC8e, ERC8f, ERC9a, E	entrolling environmental exposure for: ERC8a, ERC8b, ERC8c, ERC8d, ERC9b, ERC10a, ERC10b, ERC11a, ERC11b			
	ategories could also be possible.			
Activity	Potassium hydroxide can be used in many different chemical product categories (PC): Coatings and Paints, Fillers, Putties, Thinners (PC 9), Fertilizers (PC12), Intermediate (PC19), Products such as pH-regulators, flocculants, precipitants, neutralization agents (PC20), Washing and Cleaning Products (PC35), Water treatment chemicals (PC37), Cosmetics (PC39), Extraction agents (PC40). However, it could potentially also be used in other chemical product categories (PC 0 – 40).			
Product characteristics	Concentration of the Covers percentage substance in the product up to			
800000000181 / Version 7.0	37/45 EN			

	Substance in Mixture/Article	100 %.	
	Concentration of the Substance in Mixture/Article	The substance is used up in the process, Concentration of substance in product : 50%	
	Concentration of the Substance in Mixture/Article	Product may be diluted before use, Concentration of substance in product: > 10%, Covers percentage of substance in the product up to 75%.	
	Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 5%., Covers percentage substance ir the product up to 90%.	
	Physical Form (at time of use)	Solid, low dustiness	
	Very hygroscopic	,	
	Physical Form (at time of use)	liquid	
Frequency and duration of use	Continuous exposure	200 days/year, Continuous process	
Frequency and duration of use	Continuous exposure	8 hours/day, Continuous process	
Technical conditions and measures at process level to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Water  Comply with all local legisla	Neutralization is normally necessary before waste water is discharged into water treatment plants., Regular control of the pH value during introduction into open waters is required., In general discharges should be carried out such that pH changes in receiving surface waters are minimised., In general most aquatic organisms can tolerate pH values in the range of 6-9. This is also reflected in the description of standard OECD tests with aquatic organisms., Risk management measures related to the environment aim to avoid discharging the substance into municipal wastewater or to surface water, in case such discharges are expected to cause significant pH changes., Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system., Drift should be minimized	
		ative requirements on permitted local emission limits.	
Conditions and measures related	Type of Sewage Treatment Plant	WWTP/local STP (e.g. biological treatment)	
to sewage treatment plant	Sludge Treatment	pH adjustment	
	The pH of wastewater released and 9.	ased from manufacturing sites should be between 6	
	Waste treatment	Solutions with high pH-value must be neutralized before discharge.	
Conditions and measures related to external treatment of waste for disposal	Disposal methods	Waste should be reused or discharged to the industrial wastewater and further neutralized if needed., This material and its container must be disposed of in a safe way (e.g. by returning to a public recycling facility)., If container is empty, trast as regular municipal waste.	
	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.		

CAUSTIC POTASH SOLID (ALL GRADES)
-----------------------------------

	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.		
Product characteristics	Physical Form (at time of use)	Solid, low dustiness		
	Very hygroscopic			
	Physical Form (at time of use)	or in solution		
	Exposure time	10 - 15 min(Floor stripper, professional use )		
	Exposure duration per day	10 min(Oven cleaners, professional use )		
	Frequency of use	1 Times per day(Oven cleaners, professional use )		
Frequency and duration of use	Exposure duration per day	1 - 15 min(drain cleaner, closet cleaner, professional use )		
Trequency and duration of use	Frequency of use	1 Times per day(drain cleaner, closet cleaner, professional use )		
	Frequency of use	< 15 minutes/day(hand-mixing with intimate contact and only ppe available PROC19)		
	Frequency of use	< 15 minutes/day(Spraying, professional use PROC11)		
Human factors not influenced by risk management	Exposed skin area	Hands and forearms. 1 g/sec (Oven cleaners, Spraying)		
-	Assumes activities are at ambient temperature.(Oven cleaners, Spraying)			
Other operational conditions affecting workers exposure	Indoor or outdoor use			
Technical conditions and measures to control dispersion from source towards the worker	General exposures	Use closed systems or covering of open containers (e.g. screens) Use of pliers, grip arms with long handles with manual use to avoid direct contact and exposure by splashes (no working over one's head) Transport over pipes, technical barrel filling/emptying of barrel with automatic systems (suction pumps etc.) Automate activity where possible. Transfer via enclosed lines. Ensure material transfers are under containment or extract ventilation. Avoid splashing. Containment of liquid volumes in sumps to collect/prevent accidental spillage Provide local exhaust ventilation (LEV). or Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.		
Organisational measures to prevent /limit releases, dispersion and exposure	General exposures	Workers in the risky process/areas identified should be trained a) to avoid to work without respiratory protection and b) to understand the corrosive properties and, especially, the respiratory inhalation effects and c) to follow the safety procedures instructed by the employer.  The employer has also to ascertain that the required PPE is available Replacing, where appropriated, manual processes by automated and/or closed processes. This would		

		avoid irritating mists, sprayings and subsequent potential splashes.  Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment.  Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.  Ensure control measures are regularly inspected and maintained.  Supervision in place to check that the RMMs in place are being used correctly and OC's followed
Conditions and measures related to personal protection, hygiene and health evaluation	General exposures	In case of dust or aerosol formation: use respiratory protection with approved filter (P2) Use eye protection according to EN 166. Wear chemically resistant gloves. Wear suitable gloves tested to EN374. material: butyl-rubber, PVC, polychloroprene with natural latex liner, material thickness: 0.5 mm, breakthrough time: >480 min material: nitrile-rubber, fluorinated rubber, material thickness: 0.35-0.4 mm, breakthrough time: > 480 min If splashes are likely to occur: Wear suitable protective clothing, aprons, shield and suits Wear rubber boots. Tightly fitting safety goggles Face-shield
	General exposures	Dermal Protection Wear suitable gloves tested to EN374. Wear alkali-resistant protective clothing. (Efficiency: 95 %)

Worker can be exposed to corrosive concentrations

# 3. Exposure estimation and reference to its source

### **Environment**

ERC2, ERC8a, ERC8b: ECETOC TRA

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
ERC2, ERC8a, ERC8b		Workers exposure			< 1
ERC2, ERC8a, ERC8b		Indirect exposure to humans via the environment			<1

Substance will disassociate upon contact with water, the only effect is the pH effect, therefore after passing through the STP exposure is considered negligible and with no risk. As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

#### **Workers**

PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC19: ECETOC TRA worker v3

PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC19: Inhalation exposure

PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC19, Relevant for all PROCs: ECETOC TRA

# 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Health

Important note: By demonstrating a safe use when comparing exposure estimates with the long-term DNEL, the acute DNEL is therefore also covered (according to R.14 guidance, acute exposure levels can be derived by multiplying long-term exposure estimates by a factor of 2).

Worker exposure was modeled following worst case scenario, any deviation should be checked using ECETOC TRA tool

If measured data are not available, the DU may make use of an appropriate scaling tool such as ECETOC TRA. For further information on the assessment method, see: https://www.ecetoc.org/

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

If measured data are not available, the DU may make use of an appropriate scaling tool such as MEASE (www.ebrc.de/mease.html) to estimate the associated exposure.

Environment

If the local conditions deviate significantly from the values in the EU RAR, then further site specific evaluation is required

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Measured data could be used to confirm exposure levels are within the boundaries of the exposure scenario. The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

For further information on the assessment method, see: https://www.ecetoc.org/

Guidance is based on assumed operating conditions which may not be applicable to all sites. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

DU's can calculate their own Risk Ratios and/or PEC/PNEC ratios using DNEL's and PNEC's listed in the SDS, as well as the actual quantities of the substance, daily usage pattern, substance concentration, etc.

#### Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

High viscosity adjustment with aids (good to avoid splashes practice).

Delivery only as barrel commodity and/or in tank car (good practice).

1. Short title of Exposure Sco	enario 6: Consumer use			
Main User Groups		rivate households (= general public = consumers)		
Chemical product category	PC9a: Coatings and paints, thinners, paint removers PC35: Washing and cleaning products			
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8b: Wide dispersive indoor use of reactive substances in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems ERC8e: Wide dispersive outdoor use of reactive substances in open systems ERC9a: Wide dispersive indoor use of substances in closed systems			
Activity	Note: this Exposure Scenar the quality grade of the sub	io is only relevant for an appropriated use according to stance delivered		
2.1 Contributing scenario co ERC9a	ntrolling environmental	exposure for: ERC8a, ERC8b, ERC8d, ERC8e		
No exposure assessment pres	ented for the environment			
Activity	Potassium hydroxide can be used in many different chemical product categories (PC): Coatings and Paints, Fillers, Putties, Thinners (PC 9), Fertilizers (PC12), Intermediate (PC19), Products such as pH-regulators, flocculants, precipitants, neutralization agents (PC20), Washing and Cleaning Products (PC35), Water treatment chemicals (PC37), Cosmetics (PC39), Extraction agents (PC40). However, it could potentially also be used in other chemical product categories (PC 0 – 40).			
	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.		
Product characteristics	Physical Form (at time of use)	Solid, low dustiness		
	Physical Form (at time of use)	liquid		
Frequency and duration of use	Continuous exposure	Continuous release		
Conditions and massures related	Type of Sewage Treatment Plant	WWTP/local STP (e.g. biological treatment)		
Conditions and measures related to sewage treatment plant	Sludge Treatment	pH adjustment		
	The pH of wastewater released from manufacturing sites should be between 6 and 9.			
Conditions and measures related to external treatment of waste for disposal	d This material and its container must be disposed o			
2.2 Contributing scenario co PC28, PC35, PC39	ntrolling consumer expo	osure for: PC9a, PC9b, PC9c, PC12, PC20,		
No restriction (from PC0 to PC	40)			
	Concentration of the Substance in Mixture/Article	Concentration of substance in product: > 2%, liquid		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %., solid		
	Physical Form (at time of use)	Liquid mixture		
	Physical Form (at time of use)	Solid, low dustiness, Powder in liquid		
800000000181 / Version 7.0	42/45	EN		

Frequency and duration of use	Continuous use/release			
	Exposure time	Continuous exposure		
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	Keep out of the reach of children.  Do not apply product into ventilator openings or slots.  It is required to use resistant labelling-package to avoid its auto-damage and loss of the label integrity, under normal use and storage of the product. The lack of quality of the package provokes the physical loss of information on hazards and use instructions.  It is required that improved use instructions, and product information should always be provided to the consumers. This clearly can efficiently reduce the risk of misuse.  It is advisable to deliver only in very viscous preparations.  It is required to use completely sealed articles with a long service life maintenance.		
	Exposure routes	Inhalation exposure		
	Consumer Measures	In case of dust or aerosol formation: use respirato protection with approved filter (P2)		
	Exposure routes	Dermal exposure		
	Consumer Measures	Wear impervious chemical resistant protective gloves.		
	Consumer Measures	If splashes are likely to occur: wear tightly fitting safety goggles, face-shield		
2.3 Contributing scenario controlling consumer exposure for: PC9a, PC9b, PC9c, PC12, PC20, PC28, PC35, PC39				
No restriction (from PC0 to PC40)No restriction (from PC0 to PC40)				
	Concentration of the Substance in Mixture/Article	Concentration of substance in product: 0,25 - 2 %, liquid		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 100 % (unless stated differently)., solid		
	Physical Form (at time of use)	Liquid mixture		
	Physical Form (at time of use)	Solid, low dustiness, powder to liquid		
Amount used	The amount used per work	The amount used per worker varies from activity to activity		
	Exposure time	Continuous exposure		
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	Do not apply product into ventilator openings or slots. It is required to use resistant labelling-package to avoid its auto-damage and loss of the label integrity, under normal use and storage of the product. The lack of quality of the package provokes the physical loss of information on		
800000000181 / Version 7.0	43/45	EN		

	hazards and use instructions. It is required that improved use instructions, and product information should always be provided to the consumers. This clearly can efficiently reduce the risk of misuse. It is advisable to deliver only in very viscous preparations. It is advisable to delivery only in small amounts. Keep locked up and out of the reach of children.
Exposure routes	Dermal exposure
Consumer Measures	Wear suitable gloves. If splashes are likely to occur: wear tightly fitting safety goggles, face–shield
Exposure routes	Inhalation exposure
Consumer Measures	In case of dust or aerosol formation: use respiratory protection with approved filter (P2)

# 2.4 Contributing scenario controlling consumer exposure for: PC9a, PC9b, PC9c, PC12, PC20, PC28, PC35, PC39

No restriction (from PC0 to PC40)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product: < 0,5%, liquid
	Physical Form (at time of use)	liquid
	Exposure routes	Dermal exposure
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	Keep out of the reach of children. Do not apply product into ventilator openings or slots. It is required to use resistant labelling-package to avoid its auto-damage and loss of the label integrity, under normal use and storage of the product. The lack of quality of the package provokes the physical loss of information on hazards and use instructions. It is required that improved use instructions, and product information should always be provided to the consumers. This clearly can efficiently reduce the risk of misuse. It is advisable to deliver only in very viscous preparations. It is advisable to delivery only in small amounts.

#### 3. Exposure estimation and reference to its source

# **Environment**

Relevant for all ERCs: ECETOC TRA model v2

ERC8b, ERC9a: ECETOC TRA

Contributing Scenario	Specific conditions	Compartment	Value	Level of Exposure	RCR
Relevant for all	liquid				< 1
80000000181	/ Version 7.0	44/45			EN

ERCs				
ERC8b, ERC9a	liquid	Indirect exposure to humans via the environment	 	< 1

Consumer uses relate to already diluted products which will further be neutralized quickly in the sewer, well before reaching a WWTP or surface water. Substance will disassociate upon contact with water, the only effect is the pH effect, therefore after passing through the STP exposure is considered negligible and with no risk. Significant emissions to air are not expected due to the very low vapour pressure of the substance. Qualitative risk characterisation.

#### **Consumers**

PC9a, PC35: Other measured data

When existing controls and recommended RMMs are applied, safe use can be concluded. The substance will be rapidly neutralised as a result of its reaction with CO2 (or other acids). Since the substance concentration and amount handled are smaller compared to professional use and since the DNEL and RMMs are similar, safe use can be concluded for consumer use. The consumer Exposure through inhalation is not further quantitatively assessed. Qualitative approach used to conclude safe use. no exposure expected.

# 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Health

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Measured data could be used to confirm exposure levels are within the boundaries of the exposure scenario. The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

The DU works inside the boundaries set by the ES if either the proposed risk management measures as described above are met or the downstream user can demonstrate on his own that his operational conditions and implemented risk management measures are adequate. This has to be done by showing that they limit the inhalation and dermal exposure to a level below the respective DNEL (given that the processes and activities in question are covered by the PROCs listed above) as given below

Important note: By demonstrating a safe use when comparing exposure estimates with the long-term DNEL, the acute DNEL is therefore also covered (according to R.14 guidance, acute exposure levels can be derived by multiplying long-term exposure estimates by a factor of 2).

Safe use is demonstrated, if the calculated exposure level is below the relevant DNEL (RCR <1).

ECETOC-TRA model was used for risk assessment, but EUSES model may also be used for environmental risk. Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

#### Additional good practice advice beyond the REACH Chemical Safety Assessment

Use suitable eye protection.

Avoid inhalation of the product.

To avoid risks to human health and the environment, comply with the instructions for use.

Assumes a good basic standard of occupational hygiene is implemented.